

Clear high strength adhesive to bond many materials including carpeting, insulation materials, urethane foam, lightweight headliners, fabrics, plastics, rubber and adequately supported flexible vinyl to metal and other surfaces. It offers excellent heat, moisture and water resistance.

**PRODUCT****SIZE****PF 528**

446 g (15.75 oz) Aerosol

**READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!****IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

**NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.**

**SUITABLE SUBSTRATES:**

- Carpeting
- Insulation materials
- Urethane foam
- Lightweight headliners
- Fabrics
- Plastics
- Rubber
- Flexible vinyl
- Metal

**ADVANTAGES:**

- Adjustable spray pattern
- Resists humidity
- High strength (stronger than PF 505)

**DIRECTIONS FOR USE:**

1. Surface must be free of wax, silicone, grease, dirt and other contaminants.
2. Clean surfaces with PF 600 General Purpose Adhesive Cleaner.
3. Shake can for 1 minute after mixing ball moves freely.
4. For best results, use only when temperature of material and surfaces are between 21°C and 24°C (70°F and 75°F).
5. Select spray pattern by rotating spray head to desired position.
6. Spray can approximately 15 to 20 cm (6 to 8 inches) from surface.
7. Apply a uniform overlap coat to both bonding surfaces.
8. Let adhesive dry 2 to 3 minutes until tacky, then press together.
9. When finished, turn can upside down and spray about 3 seconds to clean out spray head. Wipe off tip.

**Caution:** Solvent in the product may harm some paint and plastic surfaces. Masking is recommended where overspray may occur. Test on hidden part to insure compatibility.

**Cleaning:** Clean excess adhesive with PF 600 General Purpose Adhesive Cleaner.

**TECHNICAL DATA:**

	<b>PF 528</b>
<b>Physical State</b>	Aerosol
<b>Color:</b>	Opaque, white
<b>Odour:</b>	Hydrocarbon odour
<b>Solubility :</b>	Not soluble in water
<b>Flash point:</b>	-26°C (-14.8°F) (estimated)
<b>Auto ignition temperature:</b>	234°C (453.2°F)
<b>VOC:</b>	3.78 lbs/usc • 452.96 g/L

**PRECAUTIONARY INFORMATION**

Refer to product label and Safety Data Sheet for health and safety information before using this product.

**SAFETY CONSIDERATION**

Safety Data Sheets are available at [www.proformproducts.com](http://www.proformproducts.com) or upon request at [info@proformproducts.com](mailto:info@proformproducts.com). These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

**TECHNICAL INFORMATION**

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

**PRODUCT USE**

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

**WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY**

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.