

Wax Based Permanent Rustproofing PF 570

Non paintable, high quality wax based rustproofing that provides durable protection. Product bonds to metal surfaces by molecular attraction. It can be used on both exterior and interior underbody surfaces.

PRODUCT	SIZE	COLOR
PF 570	390 g (13.75 oz)	Amber

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING! IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

Metals

ADVANTAGES:

- · Protects against rust, salt and corrosion
- Creeps and penetrates
- Resist abrasion

DIRECTIONS FOR USE:

- 1. Clean the surface and remove rust.
- 2. Shake can for 1 minute after mixing ball moves freely.
- 3. Spray can approximately 20 to 25 cm (8 to 10 inches) from surface.
- 4. To assure that entire contents will be dispensed, always have the dot on can rim facing toward surface to be sprayed.
- 5. Attach supplied extension tube for hard to reach areas.
- 6. When finished, turn can upside down and spray about 3 seconds to clean out sprayhead.
- 7. Clean excess with PF 600 General Purpose Cleaner.
- 8. Allow four hours before exposing to wet road conditions. This product does not dry thoroughly and remains tacky.

ATTENTION: DO NOT APPLY RUSTPROOFING MATERIAL TO THE EXHAUST SYSTEM, CATALYTIC CONVERTER, PLASTIC PARTS OR RUBBER.

TECHNICAL DATA:

	PF 570	
Physical State	Aerosol	
Color:	Amber	
Odour:	Bubble-gum	
Solubility:	Insoluble	
Flash point:	42°C (108°F) (estimate for liquid)	



Wax Based Permanent Rustproofing PF 570

Auto ignition temperature:	460°C (860°F) (propellant)
VOC:	5.46 lbs/usg • 658 g/L

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.