

Dissolves edges on 2K clearcoat applications. Ideal with medium and high solid clears. Excellent for blending single-stage paint systems. Use for spot repairs with PF 685 and PF 580. Leaves an invisible blend.

PRODUCT**SIZE****PF 581**

357 g (12.6 oz) Aerosol

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!**IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

ADVANTAGES:

- Dissolves edges on 2K clearcoat applications
- Ideal with medium and high solid clears
- Excellent for blending single-stage paint systems
- Use for spot repairs with PF 685 and PF 580
- Leaves an invisible blend

SURFACE PREPARATION:

Follow paint manufacturers recommendation for preparation of blending area.

DIRECTIONS FOR USE:

SPRAYING: Once the clearcoat has been properly applied a light mist coat of Blending Clear Solvent is applied over the blend area holding the aerosol 8 inches from the panel. The blending process is best when you apply rapid light coats of Blending Clear Solvent. The blend edge will melt into the original paint work requiring little or no processing once the clearcoat has cured. Once applied, the manufacturer's instructions for flash off and drying process should be followed. 100% UV stable and will not interfere with the durability of the OEM coating or refinished urethane coating.

DRYING: When using Blending Clear Solvent, follow clearcoat manufacturer's instructions for drying.

TECHNICAL DATA:

	PF 581
Physical State:	Aerosol
Color:	Clear, colourless, light yellow
Odour:	Characteristic odour, Acetone odour
Solubility:	Slightly soluble in water
Flash point:	44°C (111°F) Closed cup (liquid)

Auto ignition temperature:	420°C (788°F) (liquid)
MIR:	-

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.