

High quality activator formulated for use in urethane enamels, primers and clearcoats. Designed to produce a durable high gloss. Universal Urethane Activator is compatible with major paint company urethane systems.

PRODUCT	SIZE
PF 597C	946 ml (U.S. Quart)
PF 598C	473 ml (U.S. Pint)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Urethane enamels
- Primers
- Clearcoats

ADVANTAGES:

- Durable finish
- High gloss
- Better flow out

DIRECTIONS FOR USE:

Follow paint manufacturers directions for the amount of hardener to be added.

Caution: It is important to test the compatibility of this product with your paint system. Paint mixed with hardener should be used within 4 hours and can not be stored for future use. **Clean spray equipment immediately following use. Please test the compatibility of this hardener with your paint system by mixing a minimal portion of the products. Ensure it reacts properly.**

TECHNICAL DATA:

	PF 597C, PF 598C
Physical State:	Liquid
Color:	Light yellow
Odour:	Characteristic odour, Solvent odour
Solubility:	Negligible. Reacts slowly with water to liberate CO ₂ gas
Flash point:	-9°C (15.8°F)
Auto ignition temperature:	No data
VOC:	2 lbs/gal • 243.3 g/L

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.