

This General Purpose Adhesive Cleaner is a quick acting, multi-purpose automotive body work solvent, formulated to remove adhesives, silicone, wax, grease, oil, tar, cement and road film from metal, vinyl, rubber, glass, and cured paint. It will not harm most thoroughly cured automotive paint, vinyl, fabrics and plastic surfaces when properly used.

PRODUCT	SIZE
PF 600	946 ml (U.S. Quart)
PF 600-1	3.78 L (U.S. Gallon)
PF 600-5	18.9 L (5 U.S. Gallons)

**READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!
IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION. May cause softening and discoloration of Plexiglass and other similar materials.

REMOVES

- Silicone
- Wax
- Oil
- Tar
- Cement
- Road film

SUITABLE SUBSTRATES

- Metal
- Vinyl
- Rubber
- Glass
- Cured Paint

ADVANTAGES

- Efficiently cleans stubborn deposits on metal
- Quickly removes silicone, wax, oil, tar, grease and more
- Excellent for pre-sanding prep
- Leaves no residue

SURFACE PREPARATION:

1. Pour into a 4 fl oz container. Use prior to sanding. Spray surface liberally with General Purpose Adhesive Cleaner from hand held spray bottle. Let product sit for a few seconds.
2. Using a clean and dry cloth, wipe off in one direction only.

Caution: This product is not recommended for use on plastic or fiberglass, over freshly painted surfaces or over fresh primers-sealers. Soaked wipers should not be allowed to remain on finished surfaces. Do not rub hard on newly painted surfaces.

When using solvents for cleanup, use proper precautionary measures for handling and follow all proper disposal procedures.

TECHNICAL DATA:

	PF 600, PF 600-1, PF 600-5
Physical State	Liquid
Color:	Clear, colourless
Odour:	Hydrocarbon odour.
Solubility :	Not soluble in water
Flash point:	14°C (57°F) (Closed Cup)
Auto ignition temperature:	320°C (608°F)
VOC	819.6 g/L • 6.84 lbs/gal

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form’s control and uniquely within user’s knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user’s method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. (“Pro Form”) makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form’s total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.