



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 601 WATERBORNE PLASTIC PARTS CLEANER

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF 601 WATERBORNE PLASTIC PARTS CLEANER

Recommended use and restrictions on .. Cleaning solution.
use

Chemical family..... Alcohol solution.

NFPA rating..... Health: 1 Fire: 3 Reactivity: 0.

HMIS..... H: 1 F: 3 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Eye Irritation — Category 2A.

Hazard Description..... H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233
Keep container tightly closed. P240 Ground and bond container and receiving equipment.
P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take
precautionary measures against static discharge. P264 Wash thoroughly after handling.
P280 Wear protective gloves and eye protection.

Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 +
P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse
thoroughly with water and use safety shower . P305 + P351 + P338 If in eyes rinse
cautiously with water for several minutes. Remove contact lenses, if present and easy to
do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get
medical attention.

Storage..... P403 + P235 Store in well ventilated area. Keep cool.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Isopropyl Alcohol	67-63-0	30-60

SECTION 04: FIRST-AID MEASURES

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at
least 15 minutes. Obtain medical attention.

Skin contact..... Remove all contaminated clothing and immediately wash the exposed areas with copious
amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If
irritation persists, seek medical attention.

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is
difficult, give oxygen, obtain medical attention.

Ingestion..... Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with
head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an
unconscious person. If ingestion is suspected, contact physician or poison control center
immediately.

PRODUCT: PF 601 WATERBORNE PLASTIC PARTS CLEANER**SECTION 04: FIRST-AID MEASURES**

Most important symptoms and effects, Causes serious eye irritation. May cause mild skin irritation. Symptoms may include whether acute or delayed stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation.

Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing "Alcohol" foam, CO₂, dry chemical. Alcohol resistant foams (ATC type) preferred. In cases media of larger fires, water spray should be used.

Specific hazards arising from the Oxides of carbon (CO, CO₂). Hydrocarbon fumes and smoke.

hazardous product, such as the nature of any hazardous combustion products

Special protective equipment and Firefighter should be equipped with self-contained breathing apparatus and full protective precautions for fire-fighters clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill..... Ventilate. Eliminate all sources of ignition. Avoid all personal contact. Evacuate all non-essential personnel. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling..... Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks, and open flames. Store away from oxidizing and reducing materials. Store away from sunlight. Keep container closed when not in use. Peroxides can form if stored in contact with air.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Isopropyl Alcohol	200 ppm	400 ppm	400 ppm (TWA)	500 ppm	400 ppm	
	CA ON: 200 ppm (TWA), 400 ppm (STEL)					
Personal Protective Equipment	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.					
Respiratory/type.....	Liquid chemical goggles.					
Eye/type.....	Chemical resistant gloves. Natural rubber. PVC. Neoprene. Nitrile rubber. Polyethylene.					
Gloves/ type.....	Ethyl vinyl alcohol laminate (EVAL).					
Clothing/type.....	Wear adequate protective clothes.					
Footwear/type.....	Safety boots per local regulations.					
Other/type.....	Emergency showers and eye wash stations should be available.					
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation.					

PRODUCT: PF 601 WATERBORNE PLASTIC PARTS CLEANER**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance/Physical state.....	Liquid.
Colour.....	Clear, colourless.
Odour.....	Alcohol odour.
Odour threshold (ppm).....	Not available.
Vapour pressure (mm Hg).....	33 hPa @ 20C. (Isopropyl alcohol).
Vapour density (air=1).....	2.1. (isopropyl alcohol).
pH.....	No Data.
Density.....	7.52 lbs/USG; 0.901.
Relative Density (Specific Gravity).....	0.91.
Melting / Freezing point (deg C).....	< 0 °C.
Solubility.....	Completely miscible.
Initial boiling point / boiling range (deg C).....	82°C . (isopropyl alcohol).
Evaporation rate.....	1.5.
Flash point (deg C), method.....	12.0°C Closed Cup. Based on lowest flash point material. (isopropyl alcohol).
Auto ignition temperature (deg C).....	425°C .
Upper flammable limit (% vol).....	12.0.
Lower flammable limit (% vol).....	2.0.
Partition coefficient — n-octanol/water.....	Not available.
% Volatile by volume.....	100.
VOC (less water).....	7.52 lbs/USG.
Viscosity.....	Not available.

SECTION 10: STABILITY AND REACTIVITY

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.
Conditions to avoid, including static discharge, shock or vibration	Keep away from heat. May decompose at elevated temperatures. Incompatible with strong oxidizers. Strong acids. Aldehydes. Halogens.
Hazardous decomposition products.....	By fire: Dense black smoke. Oxides of carbon (CO,CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Isopropyl Alcohol	72600 mg/m3, rat (4 hr)	1870 mg/kg (oral, rat). 4059 mg/kg (dermal, rabbit)
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin.	
Skin contact.....	Slight irritant. Prolonged contact may cause defatting of tissue.	
Skin absorption.....	May be harmful if absorbed through the skin.	
Eye contact.....	Severe irritant. Can cause redness, irritation, tissue destruction.	
Inhalation (acute).....	Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.	
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.	
Ingestion.....	May be harmful if swallowed. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.	
Carcinogenicity of material.....	Isopropyl Alcohol is listed by IARC as a Group 3 Carcinogen; not classifiable as to its carcinogenicity to humans .	
Reproductive effects.....	No data on reproductive effects were found in the literature sources consulted.	

SECTION 12: ECOLOGICAL INFORMATION

Environmental.....	Do not allow to enter waters, waste water or soil.
Persistence and degradability.....	Readily biodegradable.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging	Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.
---	---

PRODUCT: PF 601 WATERBORNE PLASTIC PARTS CLEANER**SECTION 14: TRANSPORT INFORMATION**

TDG Classification.....	UN1219 - ISOPROPYL ALCOHOL, Solution, Class 3, Packing Group II - Limited Quantity Index 1L.
DOT Classification (Road).....	UN1219 - ISOPROPYL ALCOHOL, Solution, Class 3, Packing Group II . Ltd Qty (1 Liter/0.26 Gallons).
IATA Classification (Air).....	UN1219 - ISOPROPYL ALCOHOL, Solution, Class 3, Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
IMDG Classification (Marine).....	UN1219 - ISOPROPYL ALCOHOL, Solution, Class 3, Packing Group II. EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
Marine Pollutant.....	No.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status.....	On Domestic Substances List (DSL).
TSCA inventory status.....	All components are listed.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	
Section 302 - extremely hazardous substances.....	None.
Section 311/312 - hazard categories.....	Fire hazard. Immediate health.
Section 313.....	Isopropyl alcohol.
EPA hazardous air pollutants (HAPS) 40CFR63.....	None.
California Proposition 65.....	This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: OTHER INFORMATION

Prepared by:	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Review Date:.....	2021-11-15.
Date of the latest revision of the safety data sheet ..	2018-03-16