

Adhesion promoter that provides adhesion for refinishing of “problem” plastic substrates. Promotes adhesion of paints, primers, urethane and epoxy repair materials to thermoplastic olefins family of plastics (TPO).

PRODUCT	COLOR	SIZE
PF 608-8	Amber	220 ml (7.4 fl oz)
PF 726	Amber	946 ml (U.S. Quart)
PF 726-1	Amber	3.78 L (U.S. Gallon)

**READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!**

**IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

**NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.**

**SUITABLE SUBSTRATES**

- Plastic

**METHOD FOR DETERMINING TPO:**

Sand Test: Make sure the area being tested is not primed. Lightly grind the back side of the part. If it is of the TPO family, it will melt or smear. Use PF 608-8, PF 726, or PF 726-1 Adhesion promoter. If the substrate powders, it is not TPO. Do not use any adhesion promoter.

**DIRECTIONS FOR USE:**

1. See method above for determining if TPO plastic family.
2. Apply PF 608-8 or PF 726 or PF 726-1 Adhesion Promoter to the entire sanded area. Do not apply to exposed adhesive.
3. Once applied, allow 10 minutes flash time but not more than 15 minutes before you proceed with the repair.
4. If Adhesion Promoter dries more than 15 minutes, re-sand TPO plastics and re-apply PF 608-8 or PF 726 or PF 726-1 Adhesion Promoter.

**TECHNICAL DATA:**

	PF 608-8, PF 726, PF 726-1
Physical State	Liquid
Color:	Amber
Odour:	Solvent odour
Solubility :	Partially in water
Flash point:	-18°C (0°F) (estimate; lowest flash point ingredient)
Auto ignition temperature:	465°C (869°F)
VOC	442.2 g/L • 3.69 lbs/gal

**PRECAUTIONARY INFORMATION**

Refer to product label and Safety Data Sheet for health and safety information before using this product.

**SAFETY CONSIDERATION**

Safety Data Sheets are available at [www.proformproducts.com](http://www.proformproducts.com) or upon request at [info@proformproducts.com](mailto:info@proformproducts.com). These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

**TECHNICAL INFORMATION**

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

**PRODUCT USE**

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

**WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY**

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.