



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 619-5 WATERBORNE FINAL WIPE 3.78 LTRS

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF 619-5 WATERBORNE FINAL WIPE 3.78 LTRS

Recommended use and restrictions on .. Spray gun wash.
use

Chemical family..... Mixture.

NFPA rating..... Health: 1 Fire: 4 Reactivity: 0.

HMIS..... H: 1 F: 4 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Eye Irritant 2.

Hazard Description..... H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear protective gloves and eye protection. P264 Wash thoroughly after handling.

Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention.

Storage..... P403 + P235 Store in well ventilated area. Keep cool.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Acetone	67-64-1	3-7
Isopropyl Alcohol	67-63-0	1-5

SECTION 04: FIRST-AID MEASURES

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.

Skin contact..... Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.

Ingestion..... If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

PRODUCT: PF 619-5 WATERBORNE FINAL WIPE 3.78 LTRS**SECTION 04: FIRST-AID MEASURES**

Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media "Alcohol" foam, CO₂, dry chemical. In cases of larger fires, water spray should be used. Do not use water in a jet.
 Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products Oxides of carbon (CO, CO₂).
 Special protective equipment and precautions for fire-fighters Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill..... Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%). Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling..... Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.
 Conditions for safe storage, including any incompatibilities Keep away from heat, sparks, and open flames. Store away from oxidizing and reducing materials. Store away from sunlight. Keep container closed when not in use.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Acetone	250 ppm TLV	500 ppm	1,000 ppm	Not established	250 ppm	
Isopropyl Alcohol	200 ppm	400 ppm	400 ppm (TWA)	500 ppm	400 ppm	
Personal protective equipment						
Eye/type.....	Liquid chemical goggles.					
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.					
Gloves/ type.....	Chemical resistant gloves.					
Clothing/type.....	Wear adequate protective clothes.					
Footwear/type.....	Safety boots per local regulations.					
Other/type.....	Emergency showers and eye wash stations should be available.					
Appropriate engineering controls.....	Local exhaust at points of emission. Ventilation system must be designed vapor and explosion proof for handling solvent vapors.					

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Liquid.
 Colour..... Clear, colourless.
 Odour..... Solvent odour.
 Odour threshold (ppm)..... Not available.
 Vapour pressure (mm Hg)..... Not available.
 Vapour density (air=1)..... >1.
 pH..... Not available.
 Relative Density (Specific Gravity)..... 0.973.

PRODUCT: PF 619-5 WATERBORNE FINAL WIPE 3.78 LTRS**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Melting / Freezing point (deg C).....	Not Available.
Solubility.....	Complete.
Initial boiling point / boiling range (deg C).	> 56 C.
Evaporation rate.....	> 1.0.
Flash point (deg C), method.....	-18°C. (estimated).
Auto ignition temperature (deg C).....	> 400°C.
Upper flammable limit (% vol).....	12.6.
Lower flammable limit (% vol).....	2.0.
Coefficient of water/oil distribution.....	Not available.
% Volatile by volume.....	98.92.
VOC.....	48.66 g/L. 0.40689 lbs/USG.
Viscosity.....	12.5 - 13.5 sec. .

SECTION 10: STABILITY AND REACTIVITY

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Conditions to avoid, including static discharge, shock or vibration	Keep away from heat. Incompatible with strong oxidizers.
Hazardous decomposition products.....	By fire: Dense black smoke. Oxides of carbon (CO,CO2).
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Acetone	50,100 mg/m3 8 hours rat inhalation	5,800 mg/kg rat oral
Isopropyl Alcohol	16,000 ppm 8 hours rat	5,000 mg/kg rat oral. 12,800 mg/kg rabbit dermal
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	Causes serious eye irritation. Ingestion may cause adverse health effects.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .	
Carcinogenicity of material.....	This product is not listed by IARC or NIOSH or regulated as a carcinogen by OSHA.	
Teratogenicity.....	None known.	
Reproductive effects.....	No known reproductive effects.	

SECTION 12: ECOLOGICAL INFORMATION

Environmental.....	Do not allow to enter waters, waste water or soil.
Persistence and degradability.....	Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging	Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.
---	---

SECTION 14: TRANSPORT INFORMATION

TDG Classification.....	UN1993 - FLAMMABLE LIQUID, N.O.S. (Acetone) - Class 3 - Packing Group II - This product meets the Limited Quantity exemption when packaged in containers less than 1 Litre.
DOT Classification (Road).....	UN1993 - FLAMMABLE LIQUID, N.O.S. (Acetone) - Class 3 - Packing Group II - This product meets the Limited Quantity exemption when packaged in containers less than 1 Litre.
IATA Classification (Air).....	UN1993 - FLAMMABLE LIQUID, N.O.S. (Acetone) - Class 3 - Packing Group II. Limited Quantity.
IMDG Classification (Marine).....	UN1993 - FLAMMABLE LIQUID, NOS (Acetone) - Class 3 - Packing Group II - FE-SD. Limited Quantity.
Marine Pollutant.....	No.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

PRODUCT: PF 619-5 WATERBORNE FINAL WIPE 3.78 LTRS

SECTION 15: REGULATORY INFORMATION

WHMIS 1988 classification.....	B2, D2B.
CEPA status.....	On Domestic Substances List (DSL).
TSCA inventory status.....	All components are listed.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	
Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories.....	Immediate health. Fire hazard.
Section 313.....	Isopropyl alcohol.
EPA hazardous air pollutants (HAPS) 40CFR63	None.
California Proposition 65.....	*WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. *WARNING: This product contains a chemical known to the State of California to cause cancer.

SECTION 16: OTHER INFORMATION

Prepared by:	Trivalent Data Systems Ltd. www.trivalent.com .
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Date of the latest revision of the safety data sheet ..	2019-06-03