

Reducer than can be used for dilution of all water free urethane based paints and primers. Allows maximum pot life and improves flow and levelling.

PRODUCT	SIZE	
PF 682-1C	3.78 L (U.S. Gallon)	Slow
PF 682-5C	18.9 L (5 U.S. Gallons)	Slow
PF 687C	946 ml (U.S. Quart)	Medium
PF 683-1C	3.78 L (U.S. Gallon)	Medium
PF 683-5C	18.9 L (5 U.S. Gallons)	Medium
PF 684-1C	3.78 L (U.S. Gallon)	Fast
PF 684-5C	18.9 L (5 U.S. Gallons)	Fast

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

FEATURES:

- Alcohol free
- Water free
- Better flow out

DIRECTIONS:

Follow paint or primer manufacturer's directions for reduction ratios. Read all warnings and directions for safe usage and proper application.

CAUTION: It is important to test the compatibility of this product with your paint system. When using solvents for cleanup, use proper precautionary measures for handling and follow all proper local disposal procedures and regulations.

TECHNICAL DATA:

	PF 682-1C, PF 682-5C (Slow)	PF 687C, PF 683-1C, PF 683-5C (Medium)	PF 684-1C, PF 684-5C (Fast)
Physical State:	Liquid	Liquid	Liquid
Color:	Clear, colourless	Clear, colourless	Clear, colourless
Odour:	Ketone odour	Naphthalenic, sweet odour	Fruity characteristic
Solubility:	Partially in water	No data	Partially in water
Flash point:	-18°C (0°F)	-18°C (0°F)	-18°C (0°F)
Auto ignition temperature:	465°C (869°F)	No data	No data
VOC:	0.0 g/L • 0.0 lb/usg	0.0 g/L • 0.0 lb/usg	0.0 g/L • 0.0 lb/usg

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.