



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 688C 4:1 CLEARCOAT 2.1 VOC

SECTION 01: IDENTIFICATION

Product identifier..... PF 688C 4:1 CLEARCOAT 2.1 VOC
Other means of identification
Chemical family..... Polyester. Solvent solution.
Recommended use and restrictions on .. Paints.
use
Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189
24 hour emergency number:..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.
-
NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.
HMIS..... H: 2 F:4 R: 0.

SECTION 02: HAZARD IDENTIFICATION



Hazard Classification..... Flammable Liquid 2. Skin Irritation — Category 2. Skin Sensitizer — Category 1. Eye Irritation — Category 2A. Specific Target Organ Toxicity — Single Exposure — Category 3. (narcotic effects). (respiratory system).
Signal Word..... DANGER.
Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.
Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell.
Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.
Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.
Note This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Acetone	67-64-1	10-30
n-Butyl Acetate	123-86-4	10-30
4-Chlorobenzotrifluoride	98-56-6	7-13

PRODUCT: PF 688C 4:1 CLEARCOAT 2.1 VOC**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

tert-Butyl acetate	540-88-5	7-13
Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate	41556-26-7	0.1-1
<<The actual concentration(s) withheld as a trade secret>> .		

SECTION 04: FIRST-AID MEASURES

Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, whether acute or delayed	Harmful if swallowed, in contact with skin or if inhaled. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause respiratory irritation. Can cause skin sensitization. Causes skin and eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO ₂ , dry chemical. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Extremely flammable. Thermal decomposition products are toxic. May include: Oxides of carbon (CO, CO ₂). Hydrocarbons and traces of chlorine compounds.
Special protective equipment and precautions for fire-fighters	Acetone is a highly flammable liquid. It is easily ignited in the presence of heat, an ignition source such as a naked flame or a spark (including electrostatic discharge). Aqueous solutions of acetone can also ignite. Acetone vapors are heavier than air and can travel a long distance to an ignition source and cause flashback. Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	No action shall be taken involving any personal risk or without suitable training. Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Take precautions against static discharge. Use non-sparking tools and equipment to pick up the spilled material. Equipment should be grounded.
Methods and materials for containment and cleaning up	
Leak/spill.....	Avoid all personal contact. Evacuate all non-essential personnel. Ventilate. Eliminate all sources of ignition. Contain the spill. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Prevent runoff into drains, sewers, and other waterways.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....	Extremely flammable. Keep away from heat, sparks, and open flame. Ground handling equipment. Prevent accumulation of electrostatic charges. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.
------------------------------------	---

PRODUCT: PF 688C 4:1 CLEARCOAT 2.1 VOC**SECTION 07: HANDLING AND STORAGE**

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, and open flames. Keep container closed when not in use. Use explosion proof equipment in areas where vapour concentrations can become ignitable. Store away from oxidizing and reducing materials. Store away from sunlight. Store in a cool and dry place, for product integrity. Do not cut, grind or weld on or near container, do not expose containers to heat, flame, sparks, static electricity, or other sources of ignition: the containers may explode and cause injury or death.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Acetone	250 ppm TLV CA ON: 500ppm (TWA); 750ppm (STEL)	500 ppm	1,000 ppm	Not established	250 ppm
n-Butyl Acetate	50 ppm CA ON: 50ppm (TWA), 150ppm (STEL)	150 ppm	150 ppm	200 ppm	150 ppm / STEL 200 ppm
4-Chlorobenzotrifluoride	Not established	Not established	Not established	Not established	Not established
tert-Butyl acetate	200 ppm CA ON: 50ppm (TWA), 150ppm (STEL)	Not established	200 ppm	Not established	200 ppm
Bis (1,2,2,6,6-Pentamethyl-4- Piperidyl) Sebacate	Not established	Not established	Not established	Not established	Not established
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation.				
Personal Protective Equipment Gloves/ type.....	Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Contact glove supplier for recommendations.				
Eye/type.....	Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard exists.				
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.				
Clothing/type.....	Wear adequate protective clothes.				
Footwear/type.....	Safety boots per local regulations.				
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state.....	Liquid.
Colour.....	Clear.
Odour.....	Characteristic odour. Solvent odour.
Odour threshold (ppm).....	Not available.
pH.....	Not applicable.
Melting / Freezing point (deg C).....	< -33 °C.
Initial boiling point / boiling range (deg C).....	> 56 °C.
Flash point (deg C), method.....	-18°C. (estimate; lowest flash point ingredient).
Evaporation rate.....	Moderate.
Flammability (solids and gases).....	Not applicable. Flammable liquid.
Upper flammable limit (% vol).....	12.6.
Lower flammable limit (% vol).....	0.9.
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	>1.
Relative Density (Specific Gravity).....	0.984.
Pounds / USG.....	8.22.
Solubility.....	Slightly soluble in water.
Partition coefficient — n-octanol/water.....	Not available.
Auto ignition temperature (deg C).....	Not available.
Decomposition temperature.....	Not available.
Viscosity.....	14 sec Zahn #2.

PRODUCT: PF 688C 4:1 CLEARCOAT 2.1 VOC**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

% Volatile by weight..... 15.44.
 VOC (less water)..... Mixed VOC's when mixed with Activators as per label instructions: Fast; 2.08 lbs/USG (249.2 g/L). Medium; 2.08 lbs/USG (249.2 g/L). Slow; 2.08 lbs/USG (249.2 g/L).

SECTION 10: STABILITY AND REACTIVITY

Reactivity Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
 Chemical stability..... Stable at normal temperatures and pressures.
 Possibility of hazardous reactions..... Will not occur under normal temperature and pressure.
 Conditions to avoid, including static Avoid heat, spark, open flames. Electrostatic charge.
 discharge, shock or vibration
 Incompatible materials..... Strong oxidizing agents, acids, bases. Reducing agents. Aldehydes. Ammonia. Peroxides. Chlorine compounds. Acetone may ignite or react violently with strong oxidizing agents, such as chromic acid, chromium trioxide, chromyl chloride, hot nitric acid, potassium permanganate (in an alkaline medium), or peroxides.
 Hazardous decomposition products..... No hazardous decomposition products when stored and handled correctly. Hazardous decomposition products depend on temperature, air supply, and the presence of other materials. See hazardous combustion products section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Acetone	50,100 mg/m3 8 hours, rat	5,800 mg/kg (rat oral)
n-Butyl Acetate	>33 mg/L vapour, 5.2 mg/L (rat) dust/mist	10760 mg/kg (rat, oral) 14112 mg/kg (rabbit, dermal)
4-Chlorobenzotrifluoride	4479 ppm	>6,800 mg/kg (rat oral); >2,700 mg/kg (rabbit dermal)
tert-Butyl acetate	>2,230 mg/m3 4 hours rat	4,100 mg/kg (rat, oral); >2,000 mg/kg (rabbit, dermal)
Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate	Not Available	2369-3920 mg/kg (oral rat), >2000 mg/kg (dermal rabbit)
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Symptoms related to the physical, chemical and toxicological characteristics		
Effects of acute exposure.....	The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation.	
Skin contact.....	Can cause moderate irritation, defatting and dermatitis.	
Skin absorption.....	Chronic skin exposure to solvents may cause effects similar to those identified under chronic inhalation.	
Eye contact.....	Causes eye irritation. Can cause redness, irritation, tissue destruction.	
Ingestion.....	Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. May be harmful or fatal if swallowed.	
Inhalation (acute).....	Solvent vapours may be irritating to the eyes, nose and throat, resulting in redness, burning and itching of eyes, dryness of the throat and tightness in the chest. Breathing of high vapour concentrations may cause anesthetic effects and serious health effects.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.	
Inhalation (chronic).....	Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, nausea and asphyxiation.	
Carcinogenicity of material.....	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC or ACGIH.	
Reproductive effects.....	No component of this product present at levels greater than or equal to 0.1% .	
Sensitizing capability of material.....	May cause sensitization by skin contact.	
Specific Target Organ Toxicity	May cause drowsiness or dizziness. May cause respiratory irritation.	

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... Product data not available.
 Other adverse effects..... Do not allow to enter waters, waste water or soil.

PRODUCT: PF 688C 4:1 CLEARCOAT 2.1 VOC**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging

Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch.

SECTION 14: TRANSPORT INFORMATION

TDG Classification.....	UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.
DOT Classification (Road).....	UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (1 Liter). Refer to 49CRF 172.101 for additional non-bulk packaging requirements.
IATA Classification (Air).....	UN1263 - PAINT - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
IMDG Classification (Marine).....	UN1263 - PAINT - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
Marine Pollutant.....	Potential marine pollutant.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status.....	On Domestic Substances List (DSL).
TSCA inventory status.....	All components are listed.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories.....	Immediate health, delayed health, fire hazard.
Section 313.....	None above De minimus % limit.
EPA hazardous air pollutants (HAPS) 40CFR63	Toluene.
California Proposition 65.....	*** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Toluene). For more information, go to www.P65Warnings.ca.gov .

SECTION 16: OTHER INFORMATION

Prepared by:	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com .
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Date of the latest revision of the safety data sheet	2020-10-09



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 690C FAST ACTIVATOR FOR PF 688C

SECTION 01: IDENTIFICATION

Product identifier..... PF 690C FAST ACTIVATOR FOR PF 688C
Other means of identification
Chemical family..... Mixture.
Recommended use and restrictions on use .. Paints. Accelerator and activator.
Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189
24 hour emergency number:..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.
-
NFPA rating..... Health: 2 Fire: 4 Reactivity: 1.
HMIS..... H: 2 F: 4 R: 1.

SECTION 02: HAZARD IDENTIFICATION



Hazard Classification..... Flammable Liquid 2. Skin Sensitizer — Category 1. Eye Irritation — Category 2A. Acute Toxicity (Inhalation) — Category 4. Specific Target Organ Toxicity — Single Exposure — Category 3. (respiratory system). (narcotic effects). (central nervous system).
Signal Word..... DANGER.
Hazard Description..... H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.
Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell.
Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.
Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.
Note This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Homopolymer of HDI	28182-81-2	30-60
tert-Butyl acetate	540-88-5	30-60
Acetic acid, methyl ester	79-20-9	3-7

PRODUCT: PF 690C FAST ACTIVATOR FOR PF 688C**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

<<The actual concentration(s) withheld as a trade secret>> .

SECTION 04: FIRST-AID MEASURES

Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Rinse mouth with water. Do not induce vomiting.
Skin contact.....	Immediately remove all contaminated clothing, flush skin with water for at least 15 minutes. Wash clothing before reuse. If irritation persists, seek medical attention.
Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Check for and remove any contact lenses, if safe and easy to do so. Obtain medical attention.
Most important symptoms and effects, whether acute or delayed	Harmful if swallowed, in contact with skin or if inhaled. High vapour concentrations may be irritating to the respiratory tract. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause mild skin irritation. Can cause skin sensitization. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Additional information.....	In all cases, if irritation persists seek medical attention. Eye: stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation frequently. Workplace vapours have produced reversible corneal epithelial edema impairing vision. Skin: this compound is a known skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burns. If burned, treat as thermal burn. Ingestion: treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of this compound. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. Treat victims symptomatically.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	Dry chemical. Carbon dioxide. Foam. In cases of larger fires, water spray should be used. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	This material may produce a floating fire hazard. Thermal decomposition products are toxic. May include: Oxides of carbon (CO, CO ₂). Oxides of nitrogen. Hydrogen cyanide. Isocyanates. Smoke. Other potentially toxic fumes. Under hot acidic conditions: Isobutylene. Acetic acid.
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	No action shall be taken involving any personal risk or without suitable training. Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Take precautions against static discharge. Equipment should be grounded. Use non-sparking tools and equipment to pick up the spilled material.
Methods and materials for containment and cleaning up Leak/spill.....	Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%). Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.
Clean up.....	Decontaminate floor with decontamination solution, letting stand for at least 15 minutes.

SECTION 07: HANDLING AND STORAGE

PRODUCT: PF 690C FAST ACTIVATOR FOR PF 688C**SECTION 07: HANDLING AND STORAGE**

Precautions for safe handling.....	Use adequate ventilation. Do not breathe vapours, mist or dust. Wear respiratory protection if material is heated, sprayed, used in confined space, or if exposure limit is exceeded. Warning properties (irritation of the eyes, nose and throat or odour) are not adequate to prevent chronic overexposure from inhalation. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must not be exposed vapour or spray mist. Avoid skin and eye contact. Wash thoroughly after handling. Decomposition products are highly toxic and irritating. Ensure that equipment is properly bonded and grounded during filling and transferring as product may become electrostatically charged. Employee education and training are important.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks, and open flames. Store in tightly closed containers to prevent moisture contamination. Exposure to vapours of heated isocyanates can be extremely dangerous. Do not reseal if contamination is suspected. Do not store above 50 deg C.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Homopolymer of HDI	5 mg/m3	Not established	5 mg/m3	Not established	5 mg/m3
tert-Butyl acetate	200 ppm	Not established	200 ppm	Not established	200 ppm
Acetic acid, methyl ester	200 ppm	Not established	200 ppm	Not established	Not established
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation.				
Personal Protective Equipment Respiratory/type.....	Whenever concentrations of isocyanates exceed the exposure limit or are not known, respiratory protection must be worn. Use a respirator that is recommended or approved for use in isocyanate-containing environments. A positive pressure, supplied-air respirator or a self-contained breathing apparatus is recommended. Do not exceed the use limits of the respirator.				
Eye/type.....	Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard exists. Contact lenses should not be worn when working with this chemical.				
Gloves/ type.....	Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed. The following gloves are recommended :. Butyl rubber. Contact glove supplier for recommendations.				
Clothing/type.....	Wear impervious protective clothing.				
Footwear/type.....	Safety boots per local regulations.				
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees on the safe use and handling of the product.				
Medical surveillance.....	Medical supervision of all employees who handle or come in contact with isocyanates is recommended. These should include preemployment and periodic medical examinations with pulmonary function test (FEC, FVC as a minimum). Persons with asthmatic-type conditions, chronic bronchitis, other chronic respiratory diseases or recurring skin eczema or sensitization should be excluded from working with isocyanates. Once a person is diagnosed as sensitized to an isocyanate, no further exposure can be permitted.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state.....	Liquid.
Colour.....	Light yellow.
Odour.....	Characteristic odour. Slight.
Odour threshold (ppm).....	Not available.
pH.....	Not applicable.
Melting / Freezing point (deg C).....	< 0 °C.
Initial boiling point / boiling range (deg C).....	>55 C.
Flash point (deg C), method.....	-15 °C. (estimate; lowest flash point ingredient).
Evaporation rate.....	Not available.
Flammability (solids and gases).....	Not applicable. Flammable liquid.
Upper flammable limit (% vol).....	16.0.
Lower flammable limit (% vol).....	1.2.
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	Not available.
Relative Density (Specific Gravity).....	0.997.
Pounds / USG.....	8.32.

PRODUCT: PF 690C FAST ACTIVATOR FOR PF 688C**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Solubility.....	Little or none.
Partition coefficient — n-octanol/water.....	Not available.
Auto ignition temperature (deg C).....	>460°C.
Decomposition temperature.....	Not available.
Viscosity.....	14.5" Zahn#2.
% Volatile by volume.....	0.0.
VOC.....	0.0 g/L - 0.0 lb/usg.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Contact with moisture, other materials that react with isocyanates, or temperatures above 177 C, may cause polymerization.
Chemical stability.....	Stable at normal temperatures and pressures.
Possibility of hazardous reactions.....	Contact with moisture or other materials that react with isocyanates may cause polymerization.
Conditions to avoid, including static discharge, shock or vibration	Avoid heat, spark, open flames. Electrostatic charge.
Incompatible materials.....	Water, amines, strong acids and bases, strong oxidizing agents, alcohol, copper. Nitrates. Plastics.
Hazardous decomposition products.....	Hazardous decomposition products depend on temperature, air supply, and the presence of other materials. See hazardous combustion products section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Homopolymer of HDI	390-453 mg/m3 rat 4 hours	> 5,000 mg/kg (rat, oral); > 5,000 mg/kg (rabbit, dermal)
tert-Butyl acetate	>2,230 mg/m3 4 hours rat	4,100 mg/kg (rat, oral); >2,000 mg/kg (rabbit, dermal)
Acetic acid, methyl ester	16000 ppm (Rat) 4 h	LD50 5001 mg/kg oral rat LD50 5001 mg/kg dermal rabbit
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Symptoms related to the physical, chemical and toxicological characteristics		
Skin contact.....	May cause slight irritation. May cause sensitization by skin contact. Persons previously sensitized can experience allergic reaction with symptoms of reddening, itching, swelling and rash.	
Eye contact.....	Causes eye irritation. Can cause tearing, reddening and swelling. May cause temporary corneal damage. Vapours can produce irritation.	
Inhalation (acute).....	Isocyanate vapour/mists at concentrations above the exposure limits can irritate (burning sensation) the mucous membranes in the respiratory tract. This can cause a runny nose, sore throat, coughing, chest discomfort, difficult breathing and reduced pulmonary functioning. Causes runny nose, sore throat, coughing, chest discomfort, difficult breathing and reduced pulmonary functioning. Persons with preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the exposure limit with similar symptoms as well as asthma attack. Exposure well above the exposure limit may lead to bronchitis, bronchial spasm and pulmonary edema. Chemical or hypersensitive pneumonitis, with flu-like symptoms has also been reported. These symptoms can be delayed up to several hours after exposure. Breathing of high vapour concentrations may cause anesthetic effects and serious health effects. Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, nausea and asphyxiation.	
Ingestion.....	May be harmful or fatal if swallowed. May cause central nervous system effects such as headache, nausea, vomiting and weakness.	
Effects of chronic exposure.....	As a result of previous repeated overexposure or a single large dose, certain individuals develop sensitization which will cause them to react to a later exposure to product at levels well below the exposure limit. Symptoms including chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed. There are reports that once sensitized, an individual can experience these symptoms upon exposure to dust, cold air or other irritants. This increased lung sensitivity can persist for weeks and, in severe cases, for several years. Sensitization can be permanent. Prolonged or repeated exposure may cause lung damage, including a decrease in lung function. Prolonged vapour contact may cause conjunctivitis. Prolonged skin contact may cause reddening, swelling, rash, scaling, blistering, and in some cases, sensitization. Chronic exposure to organic solvents may cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.	
Carcinogenicity of material.....	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC or ACGIH.	
Reproductive effects.....	No component of this product present at levels greater than or equal to 0.1%.	

PRODUCT: PF 690C FAST ACTIVATOR FOR PF 688C**SECTION 11: TOXICOLOGICAL INFORMATION**

Sensitizing capability of material..... May cause sensitization by skin contact.
 Specific Target Organ Toxicity May cause drowsiness or dizziness. May cause respiratory irritation. Damage to central nervous system.

SECTION 12: ECOLOGICAL INFORMATION

Environmental..... No product data. Do not allow to enter waters, waste water or soil.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. Empty containers must be handled with care due to product residue.

SECTION 14: TRANSPORT INFORMATION

TDG Classification..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - This product meets the Limited Quantity exemption when packaged in containers less than 5 liters.
 DOT Classification (Road)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - Ltd Qty (1 litre). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.
 IATA Classification (Air)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
 IMDG Classification (Marine)..... UN1263 - PAINT RELATED MATERIAL - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
 Marine Pollutant..... No.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status..... On Domestic Substances List (DSL).
 TSCA inventory status..... All components are listed.
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... None above De minimus % limit.
 EPA hazardous air pollutants (HAPS) Hexamethylene diisocyanate.
 40CFR63
 California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity. For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Date of the latest revision of the safety data sheet .. 2020-10-23



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PBC 3001-4 EXTRA CUT COMPOUND

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PBC 3001-4 EXTRA CUT COMPOUND

Recommended use and restrictions on .. Compound.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 2 Reactivity: 0.

HMIS..... H: 2 F: 2 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 3. Aspiration Toxicity 1. Skin Irritation — Category 2. Eye Irritation — Category 2A. Specific Target Organ Toxicity — Repeated Exposure — Category 1. Health Hazard Not Otherwise Classified 1. Causes serious damage to the respiratory tract.

Hazard Description..... H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P280 Wear protective gloves and eye protection.

Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P331 Do NOT induce vomiting. P302 + P352 - If on skin: wash with plenty of water. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P314 - Get medical advice/attention if you feel unwell.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Naphtha (petroleum), heavy alkylate	64741-65-7	7-13
Distillates (Petroleum) Hydrotreated Light	64742-47-8	7-13
Propylene glycol monobutyl ether	5131-66-8	1-5
Monoethanolamine	141-43-5	1-5

<<The actual concentration(s) withheld as a trade secret>> .

PRODUCT: PBC 3001-4 EXTRA CUT COMPOUND**SECTION 04: FIRST-AID MEASURES**

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, whether acute or delayed	Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Can cause skin sensitization. Causes damage to organs through prolonged or repeated exposure.
Additional information.....	Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO ₂ , dry chemical. In cases of larger fires, water spray should be used. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Oxides of carbon (CO, CO ₂). Other potentially toxic fumes.
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.
Unusual fire / explosion hazards.....	Vapours may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapour source.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Avoid all personal contact. Evacuate all non-essential personnel. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Remove all possible sources of ignition in the surrounding area. Use explosion-proof or hand pumps and non-sparking tools and equipment. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.
-----------------	---

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....	Keep away from heat, sparks, and open flame. This material is a static accumulator. Prevent accumulation of electrostatic charges. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Naphtha (petroleum), heavy alkylate	525 mg/m ³	Not established	Not established	Not established	Not established
Distillates (Petroleum) Hydrotreated Light	1200 mg/m ³	197 ppm	Not established	Not established	Not established
	CA BC: 200mg/m ³ (TWA) Skin				
Propylene glycol monobutyl ether	Not Established	Not Established	Not Established	Not Established	Not Established

PRODUCT: PBC 3001-4 EXTRA CUT COMPOUND**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Monoethanolamine	3 ppm	6 ppm	Not Established	Not Established	Not Established	
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.					
Eye/type.....	Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard exists.					
Gloves/ type.....	Chemical resistant gloves.					
Clothing/type.....	Wear adequate protective clothes.					
Footwear/type.....	Safety boots per local regulations.					
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.					
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation.					

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state.....	Liquid.
Colour.....	Milky white.
Odour.....	Weak petroleum hydrocarbon.
Odour threshold (ppm).....	Not available.
Vapour pressure (mm Hg).....	No data.
Vapour density (air=1).....	>1.
pH.....	7.0 - 9.0.
Relative Density (Specific Gravity).....	7.6 lbs/USD - 0.910.
Melting / Freezing point (deg C).....	< 0 °C.
Solubility.....	Water dilutable.
Initial boiling point / boiling range (deg C).....	> 100° C.
Evaporation rate.....	<1.
Flash point (deg C), method.....	56. (Closed Cup).
Auto ignition temperature (deg C).....	246C.
Upper flammable limit (% vol).....	23.5.
Lower flammable limit (% vol).....	0.5.
Partition coefficient — n-octanol/water.....	Not available.
VOC (less water).....	1.68 lbs/USG.
Viscosity.....	1932 cps Spindle #4.

SECTION 10: STABILITY AND REACTIVITY

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. Heating above 60°C in the presence of aluminum can result in corrosion and generation of flammable hydrogen gas. .
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.
Conditions to avoid, including static	Keep away from heat. Incompatible with strong oxidizers.
discharge, shock or vibration	
Hazardous decomposition products.....	Oxides of carbon (CO,CO2). Thermal decomposition may release acrolein. Does not decompose up to 204°C (400°F).

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Naphtha (petroleum), heavy alkylate	>4000 mg/kg dermal rat	>8000 mg/kg oral rat
Distillates (Petroleum) Hydrotreated Light	>5.2 mg/L (4 hr.)	>5000 mg/kg (oral, rat), >2000 mg/kg (dermal, rabbit)
Propylene glycol monobutyl ether	>651 ppm 4 Hr Rat	2,700 mg/kg Rat Oral >2,000 mg/kg Rat Skin
Monoethanolamine	232 ppm Guinea Pig	1720 mg/kg Rat Oral 1018 mg/kg Rabbit Dermal
Route of exposure.....	Eye contact. Skin contact. Inhalation.	

PRODUCT: PBC 3001-4 EXTRA CUT COMPOUND**SECTION 11: TOXICOLOGICAL INFORMATION**

Effects of acute exposure.....	The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. May be harmful if absorbed through the skin.
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin.
Carcinogenicity of material.....	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC or ACGIH.
Reproductive effects.....	No known reproductive effects.
Sensitizing capability of material.....	May cause sensitization by skin contact.
Specific Target Organ Toxicity	Causes damage to organs through prolonged or repeated exposure .

SECTION 12: ECOLOGICAL INFORMATION

Environmental.....	Do not allow to enter waters, waste water or soil.
Persistence and degradability.....	Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging	Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.
---	---

SECTION 14: TRANSPORT INFORMATION

TDG Classification.....	UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillate) - Class 3 - Packing Group III - This product meets limited quantity exemption when shipped in containers less than 5 litres.
DOT Classification (Road).....	UN1993 - FLAMMABLE LIQUID, N.O.S. (Petroleum distillates) - Class 3 - PGIII - Ltd Qty (5 Liters/1.3 Gallons).
IATA Classification (Air).....	UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillates) - Class 3 - Packing Group III . Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
IMDG Classification (Marine).....	UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Solvent naphtha) - Class 3 - Packing Group III . Ems: F-E, S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
Marine Pollutant.....	No.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status.....	On DSL, or exempt.
TSCA inventory status.....	All components are either listed or exempt from the TSCA. .
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories.....	Immediate health, delayed health, fire hazard.
Section 313.....	Aluminum Oxide (fibrous forms only).
EPA hazardous air pollutants (HAPS) 40CFR63	Methylene Chloride (Dichloromethane). 1,3-Dichloropropene.
California Proposition 65.....	*** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Dichloroprene). (Ethyl acrylate). (Methylene chloride). For more information, go to www.P65Warnings.ca.gov .

SECTION 16: OTHER INFORMATION

Prepared by:	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com .
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Review Date:.....	2021-11-04.

PRODUCT: PBC 3001-4 EXTRA CUT COMPOUND**SECTION 16: OTHER INFORMATION**

Date of the latest revision of the safety .. 2018-07-12
data sheet