

Non-Paintable Rubberized Undercoat PF 701, PF 701-1, PF 701-5

A rubberized asphalt coating that contains cellulose fibres which adds strength and prevents chipping, cracking and peeling. Ideal for sealing repairs, sound deadening and rust proofing properties in wide range of hot and cold temperatures.

PRODUCT	SIZE	COLOR
PF 701	850 ml (28.7 fl oz)	Black
PF 701-1	3.78 L (U.S. Gallon)	Black
PF 701-5	18.9 L (5 U.S. Gallons)	Black

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Metals
- Plastics
- House gutters
- Fence posts
- Trees after pruning

ADVANTAGES:

- Prevents rust
- Performs in hot and cold temperatures
- Contain cellulose fibres which adds strength
- Sound deadens

SURFACE PREPARATION:

Surfaces should be clean and dry. Heavy accumulations of dirt, moisture and debris should be removed, paying particular attention to fender beads and pockets that might trap dirt and road salts.

APPLICATION:

Ready to use. Can be reduced with mineral spirits. Should not be mixed with any other product. Shake and stir well before application. For application of PF 701 - 850 ml: use PF 809 syphon gun applicator gun. For PF 701-1 3.78 L plastic jug: use PF 798 syphon gun with 36" extension hose. Can also be poured into a 850 ml empty can. Apply one heavy coat.

Avoid applying undercoat to wiring or rubber.

Dry to touch and ready to drive off in 8 hours. Reduce with mineral spirits. **DO NOT REDUCE WITH LACQUER THINNER.**

CAUTION: DO NOT APPLY THE EXHAUST SYSTEM, DRIVE SHAFT, TRANSMISSION, OIL PAN, BRAKE COMPONENTS, SUSPENSION OR SENSORS.

TECHNICAL DATA:

	PF 701, PF 701-1, PF 701-5
Physical State	Liquid
Color:	Black
Odour:	Mild, Hydrocarbon odour.
Solubility :	No data
Flash point:	40.5°C (104.9°F)(Closed Cup)
Auto ignition temperature:	232°C (450°F)
VOC:	2.73 lbs/usg • 327.14 g/L

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form’s control and uniquely within user’s knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user’s method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. (“Pro Form”) makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form’s total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.