

Non paintable, high quality paraffin base rustproofing that provides durable protection. Product bonds to metal surfaces by molecular attraction. It can be used on both exterior and interior surfaces.

PRODUCT	SIZE	COLOR
PF 708-1	3.78 L (U.S. Gallon)	Amber
PF 708-5	18.9 L (5 U.S. Gallons)	Amber
PF 708-15	58 L (15 U.S. Gallons)	Amber
PF 708-55	205 L (55 U.S. Gallons)	Amber

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES:

- Metals

ADVANTAGES:

- Never become brittle or loses adhesion
- Protects against rust, salt and corrosion
- Creeps and penetrates
- Resist abrasion

DIRECTIONS FOR USE:

1. Clean the surface and remove rust.
2. Allow four hours before exposing to wet road conditions.
3. This product is not recommended for application in temperatures below 16°C (60°F).

CAUTION: FOR METAL APPLICATIONS ONLY! DO NOT APPLY TO SMC, FIBREGLASS, PLASTIC OR RUBBER COMPONENTS. FOR METAL VERIFICATION, USE A MAGNET.

TECHNICAL DATA:

	PF 708-1, PF 708-5, PF 708-15, PF 708-55
Physical State	Liquid
Color:	Amber
Odour:	Light solvent, sweet odour
Solubility :	Insoluble
Flash point:	60°C (140°F)
Auto ignition temperature:	> 100°C (> 212°F)
VOC:	2.63 lbs/usg • 315 g/L



Product Data Sheet

Wax Based Permanent Rustproofing

PF 708-1, PF 708-5, PF 708-15, PF 708-55

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.