



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF712-15 HYBRID RUSTPROOFING BLUISH 58LTR

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF712-15 HYBRID RUSTPROOFING BLUISH 58LTR

Recommended use and restrictions on .. Rust proofing.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 2 Reactivity: 0.

HMIS..... H: 2 F: 2 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 3. Specific Target Organ Toxicity — Repeated Exposure — Category 1.
H226 Flammable liquid and vapour. H372 Causes damage to organs through prolonged or repeated exposure. (central nervous system).

Hazard Description.....

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear protective gloves and eye protection. P260 Do not breathe mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product.

Response P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P314 - Get medical advice/attention if you feel unwell.

Storage..... P403 + P235 Store in well ventilated area. Keep cool.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Solvent naphtha medium aliphatic	64742-88-7	30-50
Propylene carbonate	108-32-7	0.5-1.5

SECTION 04: FIRST-AID MEASURES

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.

Skin contact..... Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.

Ingestion..... Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.

PRODUCT: PF712-15 HYBRID RUSTPROOFING BLUISH 58LTR**SECTION 04: FIRST-AID MEASURES**

Additional information..... Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing "Alcohol" foam, CO₂, dry chemical. In cases of larger fires, water spray should be used.
media Do not use water in a jet.
Specific hazards arising from the Oxides of carbon (CO, CO₂).
hazardous product, such as the nature of
any hazardous combustion products
Special protective equipment and Firefighter should be equipped with self-contained breathing apparatus and full protective
precautions for fire-fighters clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed
containers with cold water spray. Heat will cause pressure buildup and may cause
explosive rupture. Solvent vapours may be heavier than air and may build up and travel
along the ground to an ignition source, which may result in a flash back to the source of the
vapours. Keep run-off water from entering sewers and other waterways. Dike for water
control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill..... Ventilate. Eliminate all sources of ignition. Avoid all personal contact. Contain the spill.
Spilled material and water rinses are classified as chemical waste, and must be disposed
of in accordance with current local, provincial, state, and federal regulations. Evacuate all
non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb
with earth, sand, or another dry inert material. Shovel into suitable unsealed containers,
transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of
water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated
ammonia (3-8%) and detergent (2%).

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling..... Handle and open container with care. Keep away from heat, sparks, and open flame.
Ground handling equipment. Always adopt precautionary measures against build-up of
static which may arise from appliances, handling and the containers in which product is
packed. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate
breathing apparatus. Avoid breathing vapours or mist. Employees should wash hands and
face before eating or drinking.
Conditions for safe storage, including any incompatibilities Keep container closed when not in use. Keep away from heat, sparks, and open flames.
Store away from oxidizing and reducing materials. (min/max): 10/30 C.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Solvent naphtha medium aliphatic	Not established	Not established	Not established	Not established	Not established	Not established
Propylene carbonate	Not established		Not established		Not established	Not established
Personal Protective Equipment						
Eye/type.....		Liquid chemical goggles.				
Gloves/ type.....		Chemical resistant gloves. Neoprene. Nitrile rubber.				
Clothing/type.....		Wear adequate protective clothes.				
Footwear/type.....		Safety boots per local regulations.				
Respiratory/type.....		Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.				
Other/type.....		Emergency showers and eye wash stations should be available.				
Appropriate engineering controls.....		Local exhaust at points of emission. Ventilation system must be designed vapor and explosion proof for handling solvent vapors.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Liquid.
Colour..... Black/Blue.
Odour..... Light solvent. Sweet odour.
Odour threshold (ppm)..... Not available.
pH..... Not applicable.
Melting / Freezing point (deg C)..... No data.

PRODUCT: PF712-15 HYBRID RUSTPROOFING BLUISH 58LTR**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Initial boiling point / boiling range (deg C).	No data.
Flash point (deg C), method.....	60°C (140°F).
Evaporation rate.....	<1.
Upper flammable limit (% vol).....	No data.
Lower flammable limit (% vol).....	No data.
Vapour pressure (mm Hg).....	No data.
Vapour density (air=1).....	>1.
Relative Density (Specific Gravity).....	0.7 - 0.9.
Solubility.....	Insoluble in water.
Partition coefficient — n-octanol/water.....	Not available.
Auto ignition temperature (deg C).....	> 100.
% Volatile by volume.....	<90.
VOC (less water).....	315 g/L.
Viscosity.....	>20.5 cSt @ 40C.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Chemical stability.....	Stable at normal temperatures and pressures.
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.
Conditions to avoid, including static discharge, shock or vibration	Keep away from heat. Static discharge. Incompatible with strong oxidizers.
Incompatible materials.....	Strong oxidizing agents.
Hazardous decomposition products.....	By fire: Dense black smoke. Oxides of carbon (CO,CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Solvent naphtha medium aliphatic	>1,400 ppm	3160 mg/kg oral rat
Propylene carbonate	Not available	>5000 mg/kg (oral, rat) >2000 mg/kg (dermal, rat)
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Skin contact.....	Can cause moderate irritation, defatting and dermatitis.	
Skin absorption.....	May be harmful if absorbed through the skin.	
Eye contact.....	Can cause tearing, reddening and swelling.	
Ingestion.....	May be harmful if swallowed. Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.	
Inhalation (acute).....	Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.	
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.	
Carcinogenicity of material		
Reproductive effects.....	No known reproductive effects.	

SECTION 12: ECOLOGICAL INFORMATION

Environmental.....	Do not allow to enter waters, waste water or soil.
Persistence and degradability.....	Not readily biodegradable.
Mobility in soil.....	Low mobility.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging	This material and its container must be disposed of as hazardous waste. Avoid release to the environment.
---	---

PRODUCT: PF712-15 HYBRID RUSTPROOFING BLUISH 58LTR**SECTION 14: TRANSPORT INFORMATION**

TDG Classification.....	UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillates) - Class 3 - PGIII - Regulated in bulk only. This product is a flammable liquid, Class 3, Packing Group III material with a flash point >37.8C and is exempt from the application of these regulations in non-bulk (< 450L) packaging as per TDG 1.33.
IATA Classification (Air).....	UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillates) - Class 3 - Packing Group III .
IMDG Classification (Marine).....	UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Petroleum distillates) - Class 3 - PGIII - EmS: F-E, S-E.
Marine Pollutant.....	No.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

WHMIS 1988 classification.....	B3.
CEPA status.....	Not determined.
TSCA inventory status.....	All components are listed.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	
Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories.....	Immediate health, delayed health, fire hazard.
Section 313.....	None.
EPA hazardous air pollutants (HAPS) 40CFR63	None.
California Proposition 65.....	This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: OTHER INFORMATION

Prepared by:	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Review Date:.....	2021-11-09.
Date of the latest revision of the safety .. data sheet	2017-07-10