

A tough, flexible and textured coating that can be painted. It will provide good protection against road abrasion and weathering. Excellent adhesion to metals and plastics.

PRODUCT	SIZE	COLOR
PF 714C	850 ml (28.7 fl oz)	Off White
PF 714-1C	3.78 L (U.S. Gallon)	Off White
PF 715C	850 ml (28.7 fl oz)	Black
PF 715-1C	3.78 L (U.S. Gallon)	Black
PF 715-5C	18.9 L (5 U.S. Gallons)	Black
PF 715-55C	205 L (55 U.S. Gallons)	Black

**READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!**

**IMPORTANT! This product contains hazardous materials.**

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

**NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.**

**SUITABLE SUBSTRATES:**

- Metals
- Plastics

**ADVANTAGES:**

- Resists abrasion
- Remains flexible
- Sound deadens
- Can be painted with most automotive paint

**DIRECTIONS FOR USE:**

Lightly sand to enhance bond. Surface should be prepared as for any final finish.

1. Clean surface with water and soap.
2. Clean fully cured paint surfaces with PF 605 Wax and Grease Remover (Strong). For plastic surfaces with PF 606 Plastic Parts Cleaner. For newly painted surfaces use PF 603 Wax and Grease Remover (Mild).
3. Shake thoroughly before using.
4. Using a syphon gun at 40-80 psi, adjust air pressure and spraying distance to match factory texture.
5. Under normal conditions, allow 1½ to 2 hours drying time. Make sure coating is fully cured before top coating.
6. When top coating, apply a first thin coat. Allow 5 minutes flash time. Follow with a full wet coat.

**Caution:** It is important to test the compatibility of this product with your paint system. This product is not recommended for use in temperatures below 16°C (60°F). The use below these temperatures will effect dry times and performance.

## TECHNICAL DATA:

	PF 714C, PF 714-1C	PF 715C, PF 715-1C, PF 715-5C, PF 715-55C
Physical State	Liquid	
Color:	Off White	Black
Odour:	Characteristic odour, camphor-like	Solvent odour, Camphor-like
Solubility :	Negligible	Negligible
Flash point:	4°C (39.2°F)(estimate; lowest flash point ingredient)	
Auto ignition temperature:	>190°C (> 374°F)	> 200°C (> 392°F)
VOC:	242.06 g/L • 2.02 lb/usg	1.7 lb/usg • 203.7 g/L

## PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

## SAFETY CONSIDERATION

Safety Data Sheets are available at [www.proformproducts.com](http://www.proformproducts.com) or upon request at [info@proformproducts.com](mailto:info@proformproducts.com). These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

## TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

## PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

## WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.