

A powerful formula that removes rust from steel, chrome and iron. It eliminates sanding and leaves a protective coating to inhibit further rust formation. Ideal for automobiles, trucks, bikes, tools, barbeques and all chrome plated items. **Must be topcoated.**

PRODUCT	COLOR	SIZE
PF 789-4	Amber	U.S. Pint (473 ml)
PF 789	Amber	U.S. Quart (946 ml)

READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

SUITABLE SUBSTRATES

- Steel
- Iron
- Chrome plated items

ADVANTAGES

- Stops residual rust
- Seals against residue

DIRECTIONS FOR USE:

1. Read all directions and cautions prior to use for safe and proper use. Wear rubber gloves.
2. Make sure the surface temperature is cool.
3. Shake well before using.
4. Using a brush, apply generously over the rusted area and brush vigorously until rust disappears.
5. Allow to dry and then rinse with water.
6. Repeat application for heavy rusted out areas and allow to dry for an extra ten minutes before rinsing with water. If splashed on painted areas, wash off immediately. Must be topcoated.

TECHNICAL DATA:

	PF 789-4, PF 789
Physical State	Liquid
Color:	No data
Odour:	Characteristic odour
Solubility :	Soluble
Flash point:	62°C (144°F) (estimate; lowest flash point ingredient)
Auto ignition temperature:	No data
VOC	276.8 g/l • 2.31 lbs/gal

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.