



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 827 RUSTPROOFING RUBBER PLUGS 1/2" HOLLOW 1000/BX

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF 827 RUSTPROOFING RUBBER PLUGS 1/2" HOLLOW 1000/BX

Recommended use and restrictions on .. Automotive.
use

Chemical family..... Article.

NFPA rating..... Health: 0 Fire: 0 Reactivity: 0.

24 hour emergency number:..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION

Signal Word..... Not a classified or a controlled product.

Hazard Classification..... Not classified.

Hazard Description..... Not classified.

Prevention..... No special precautions necessary.

Note This product does not meet the OSHA Hazard Communication, Globally Harmonized System or Workplace Hazardous Materials Information System criteria as a controlled or classified product.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
----------------------------	-------	-------

PRODUCT IS AN ARTICLE AND NOT A CHEMICAL

SECTION 04: FIRST-AID MEASURES

Eye contact..... Flush for 15 minutes using plenty of water. If irritation persists seek medical attention.

Skin contact..... Rinse skin with cold water. Do not peel solidified product off the skin.

Inhalation..... No specific treatment is necessary since this material is not likely to be hazardous by inhalation.

Ingestion..... Not applicable.

Most important symptoms and effects, Not applicable.
whether acute or delayed

Additional information..... In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing Use extinguishing media for surrounding fire.
media

Specific hazards arising from the Oxides of carbon (CO, CO2).
hazardous product, such as the nature of
any hazardous combustion products

Special protective equipment and Firefighter should be equipped with self-contained breathing apparatus and full protective
precautions for fire-fighters clothing to protect against potentially toxic and irritating fumes.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill..... Pick up solids and put in a dust bin. Leak/spill.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling..... Employees should wash hands and face before eating or drinking. Keep container closed
when not in use. Keep away from heat, sparks, and open flame.

Conditions for safe storage, including any Store in a cool area, away from all sources of heat and ignition. Keep away from foodstuffs.
incompatibilities

PRODUCT: PF 827 RUSTPROOFING RUBBER PLUGS 1/2" HOLLOW 1000/BX**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
-------------	-----	-------------------	-----	------------------	-----	-------

Respiratory/type..... Not generally required; if desired, use a MSHA/NIOSH approved respirator.
 Eye/type..... Recommended but not required.
 Gloves/ type..... Not normally required. Where contact may occur with hot material, wear thermal resistant gloves.
 Clothing/type..... Not normally required.
 Footwear/type..... Safety boots per local regulations.
 Other/type..... Educate and train employees on the safe use and handling of the product.
 Appropriate engineering controls..... Local exhaust ventilation or process equipment may be needed to control particulate exposures.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state..... Pellets. Granules.
 Colour..... White.
 Odour..... Faint. Hydrocarbon odour.
 Odour threshold (ppm)..... Not applicable.
 Vapour pressure (mm Hg)..... Not applicable.
 Vapour density (air=1)..... Not applicable.
 pH..... Not applicable.
 Relative Density (Specific Gravity)..... Not available.
 Melting / Freezing point (deg C)..... Not applicable.
 Melting point (deg c)..... 110.
 Solubility..... Insoluble.
 Initial boiling point / boiling range (deg C). Not applicable.
 Evaporation rate..... Not applicable.
 Flash point (deg C), method..... 260°C Closed Cup.
 Auto ignition temperature (deg C)..... Not applicable.
 Upper flammable limit (% vol)..... Not applicable.
 Lower flammable limit (% vol)..... No Data.
 Partition coefficient — n-octanol/water..... No data.
 VOC (less water)..... No VOCs.
 Viscosity..... No data.

SECTION 10: STABILITY AND REACTIVITY

Chemical stability..... This is a stable material.
 Reactivity Avoid heat, sparks and flames. Avoid temperatures over 343C.
 Conditions to avoid, including static Incompatible with fluorine and strong oxidizing agents.
 discharge, shock or vibration
 Hazardous decomposition products..... Flammable hydrocarbons.
 Possibility of hazardous reactions..... Will not occur under normal temperature and pressure.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
-------------	------	------

Route of exposure..... Not expected to pose any hazards.
 Effects of acute exposure..... Exposure to hot molten material may cause thermal burns.
 Effects of chronic exposure..... Not applicable.
 Carcinogenicity of material..... The components of this product are not listed by IARC, NTP or regulated as a carcinogen by OSHA.
 Reproductive effects..... None.

SECTION 12: ECOLOGICAL INFORMATION

Persistence and degradability..... Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

PRODUCT: PF 827 RUSTPROOFING RUBBER PLUGS 1/2" HOLLOW 1000/BX

SECTION 14: TRANSPORT INFORMATION

TDG Classification.....	Not regulated.
DOT Classification (Road).....	Not regulated.
IATA Classification (Air).....	Not regulated.
IMDG Classification (Marine).....	Not regulated.
Marine Pollutant.....	No.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status.....	This is an article and not subject to the DSL.
SARA Title III	
Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories	None.
Section 313	None.
EPA hazardous air pollutants (HAPS) 40CFR63	None.
California Proposition 65	This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: OTHER INFORMATION

Prepared by:	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Review Date:.....	2021-11-15.
Date of the latest revision of the safety data sheet ..	2018-05-28