



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF88102-1 JET BLACK BASECOAT w CONVERTER

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF88102-1 JET BLACK BASECOAT w CONVERTER

Recommended use and restrictions on use .. Paints. This product should not be used for any other purpose other than the ones described in this section.

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Skin Irritation — Category 2. Skin Sensitizer — Category 1. Eye Irritant 2. Carcinogenicity — Category 2. Reproductive Toxicity — Category 2.

Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H351 This product contains ingredients that are suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear protective gloves and eye protection. P264 Wash hands thoroughly after handling. P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood.

Response P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P302 + P352 - If on skin: wash with plenty of water. P321 - For specific treatment see section 4 on this SDS. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P362 + P364 - Take off contaminated clothing and wash before reuse. P308 + P313 If exposed or concerned, get medical advice/attention.

Storage..... P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|---------------------------------|-----------|-------|
| n-Butyl Acetate | 123-86-4 | 25-35 |
| tert-Butyl acetate | 540-88-5 | 10-20 |
| 4-Chlorobenzotrifluoride | 98-56-6 | 7-13 |
| 2-Propanol, 1-methoxy-, acetate | 108-65-6 | 1-5 |
| Xylene | 1330-20-7 | 1-5 |
| Acetone | 67-64-1 | 1-5 |

PRODUCT: PF88102-1 JET BLACK BASECOAT w CONVERTER**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

| | | |
|---|------------|------|
| Carbon Black | 1333-86-4 | 1-5 |
| Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate | 41556-26-7 | <0.5 |
| Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester | 82919-37-7 | <0.5 |

SECTION 04: FIRST-AID MEASURES

| | |
|-----------------------------|--|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Consult a physician if irritation continues. |
| Skin contact..... | Immediately remove all contaminated clothing; flush skin with water for at least 15 minutes. Wash clothing before reuse. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. |
| Additional information..... | Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable and unsuitable extinguishing media | Carbon dioxide, dry chemical, foam. |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Oxides of carbon (CO, CO ₂). Smoke. Chlorine gases and fluorine containing gases can be produced. Other potentially toxic fumes. |
| Special protective equipment and precautions for fire-fighters | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. |

SECTION 06: ACCIDENTAL RELEASE MEASURES

| | |
|-----------------|--|
| Leak/spill..... | Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear proper protective equipment. Eliminate all sources of ignition. Ventilate area to remove the remaining vapours. Absorb with an inert dry material and place in an appropriate waste container. The spill area should then be washed down with soap and water to dilute and remove remaining traces of material. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. |
|-----------------|--|

SECTION 07: HANDLING AND STORAGE

| | |
|--|---|
| Precautions for safe handling..... | Avoid skin and eye contact. Avoid breathing vapours or mist. Keep away from heat, sparks, and open flame. Containers must be grounded and bonded. Do not use near sources of ignition, open flames or sparks. Do not cut, drill, weld or grind on or near the container. Open containers slowly to allow for any pressure build-up to escape. Keep containers closed when not in use. Employees should wash hands and face before eating or drinking. |
| Conditions for safe storage, including any incompatibilities | Store in a cool, dry and well ventilated area. Keep away from heat, sparks, and open flames. Store away from oxidizing and reducing materials. |

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | ACGIH TLV | | PEL | OSHA PEL | | NIOSH |
|---------------------------------|-----------------------------------|-----------------|-----------------|-----------------|------------------------|-------|
| | TWA | STEL | | REL | STEL | |
| n-Butyl Acetate | 50 ppm | 150 ppm | 150 ppm | 200 ppm | 150 ppm / STEL 200 ppm | |
| | CA ON: 50ppm (TWA), 150ppm (STEL) | | | | | |
| tert-Butyl acetate | 200 ppm | Not established | 200 ppm | Not established | 200 ppm | |
| | CA ON: 50ppm (TWA), 150ppm (STEL) | | | | | |
| 4-Chlorobenzotrifluoride | Not established | Not established | Not established | Not established | Not established | |
| 2-Propanol, 1-methoxy-, acetate | 50 ppm | 75 ppm | Not established | Not established | Not established | |

PRODUCT: PF88102-1 JET BLACK BASECOAT w CONVERTER**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL NIOSH |
|---|---|-------------------|-----------------|------------------|-----------------|
| Xylene | 50 ppm CA ON: 100ppm (TWA); 150ppm (STEL) | 150 ppm | 100 ppm TWA | Not established | Not established |
| Acetone | 250 ppm TLV CA ON: 500ppm (TWA); 750ppm (STEL) | 500 ppm | 1,000 ppm | Not established | 250 ppm |
| Carbon Black | 3 mg/m3 CA ON: 3 mg/m3 (Inhalable) TWA | Not established | 3.5 mg/m3 | Not established | 3.5 mg/m3 |
| Bis (1,2,2,6,6-Pentamethyl-4- Piperidyl) Sebacate | Not established | Not established | Not established | Not established | Not established |
| Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-pi peridinyl ester | Not Established | Not Established | Not Established | Not Established | Not Established |
| Eye/type..... | Chemical safety goggles. Chemical safety goggles and full faceshield if a splash hazard exists. | | | | |
| Gloves/ type..... | Chemical resistant gloves. | | | | |
| Clothing/type..... | Wear adequate protective clothes. Wear long sleeves and trousers to prevent dermal exposure. | | | | |
| Footwear/type..... | Safety boots per local regulations. | | | | |
| Respiratory/type..... | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Use NIOSH approved respirator or equipment. Do not exceed the use limits of the respirator. | | | | |
| Other/type..... | Eye wash facility and emergency shower should be in close proximity. | | | | |
| Appropriate engineering controls..... | Use local exhaust or general room ventilation sufficient to prevent overexposure. | | | | |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|------------------------|
| Appearance/Physical state..... | Liquid. |
| Odour..... | Solvent odour. |
| Odour threshold (ppm)..... | Not available. |
| Vapour pressure (mm Hg)..... | Not available. |
| Vapour density (air=1)..... | >1. |
| pH..... | Not applicable. |
| Relative Density (Specific Gravity)..... | 8.17 lb/USG - 0.978. |
| Melting / Freezing point (deg C)..... | Not available. |
| Solubility..... | No data. |
| Initial boiling point / boiling range (deg C)..... | Not available. |
| Evaporation rate..... | Not available. |
| Flash point (deg C), method..... | -18°C. |
| Auto ignition temperature (deg C)..... | 535°C (995°F). |
| Upper flammable limit (% vol)..... | 7.6. |
| Lower flammable limit (% vol)..... | 1.2. |
| Partition coefficient — n-octanol/water..... | Not available. |
| VOC (less water)..... | 3.48 lb/USG - 417 g/L. |
| Viscosity..... | Not available. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|---|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. A component in this product can form peroxides of unknown stability. |
| Conditions to avoid, including static discharge, shock or vibration | Incompatible with strong oxidizers. Bases. Mineral acids. Sulfuric acids. |
| Hazardous decomposition products..... | See hazardous combustion products section 5. |
| Possibility of hazardous reactions..... | Will not occur under normal temperature and pressure. |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 | |
|-----------------|-------------------------------------|----------|---|
| n-Butyl Acetate | >33 mg/L vapour, (rat) dust/mist | 5.2 mg/L | 10760 mg/kg (rat, oral) 14112 mg/kg (rabbit, dermal) |

PRODUCT: PF88102-1 JET BLACK BASECOAT w CONVERTER**SECTION 11: TOXICOLOGICAL INFORMATION**

| INGREDIENTS | LC50 | LD50 |
|---|---|--|
| tert-Butyl acetate | >2,230 mg/m ³ 4 hours rat | 4,100 mg/kg (rat, oral); >2,000 mg/kg (rabbit, dermal) |
| 4-Chlorobenzotrifluoride | 4479 ppm | >6,800 mg/kg (rat oral); >2,700 mg/kg (rabbit dermal) |
| 2-Propanol, 1-methoxy-, acetate | Not Available | 8,532 mg/kg rat oral 5,000 mg/kg dermal rabbit |
| Xylene | 6350 ppm 4 hours rat | >3523 mg/kg rat oral |
| Acetone | 50,100 mg/m ³ 8 hours, rat | 5,800 mg/kg (rat oral) |
| Carbon Black | Not available | >10,000 mg/kg oral rat 3,000 mg/kg dermal rabbit |
| Bis (1,2,2,6,6- Pentamethyl-4- Piperidyl) Sebacate | Not Available | 2369-3920 mg/kg (oral rat), >2000 mg/kg (dermal rabbit) |
| Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester | Not Available | 3,230 mg/kg rat, oral |
| Route of exposure..... | Eye contact. Skin contact. Inhalation. | |
| Effects of acute exposure..... | Causes skin irritation. May cause moderate to severe eye irritation. Irritating to mucous membranes and upper respiratory tract. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Excessive inhalation of this product may cause dizziness. | |
| Effects of chronic exposure..... | Reports have associated repeated or prolonged overexposure to solvents with permanent brain and nervous system damage. Prolonged or repeated skin contact may cause drying or cracking of skin. Possible damage to liver and kidneys. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. | |
| Carcinogenicity of material..... | IARC has classified Carbon Black as "Group 2B", possibly carcinogenic to humans, based on laboratory animal inhalation studies. Carbon black is known to the State of California to cause cancer and developmental effects. | |
| Reproductive effects..... | Xylene has been classified by The Commission on Health and Safety as causing reproductive effects. High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known. | |

SECTION 12: ECOLOGICAL INFORMATION

Environmental..... Do not allow to enter waters, waste water or soil. May be harmful to aquatic life.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Do not heat or cut empty containers with electric or gas torch. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG Classification..... UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.

DOT Classification (Road)..... UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (1 Liter). Refer to 49CRF 172.101 for additional non-bulk packaging requirements.

IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II.

IMDG Classification (Marine)..... UN1263 - PAINT - Class 3 - Packing Group II - EmS: F-E S-E.

Marine Pollutant..... Potential marine pollutant.

Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status..... A component of this product is on the NDSL.

OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.

SARA Title III

Section 302 - extremely hazardous substances None.

Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.

Section 313..... Xylene.

PRODUCT: PF88102-1 JET BLACK BASECOAT w CONVERTER

SECTION 15: REGULATORY INFORMATION

EPA hazardous air pollutants (HAPS) None.
 40CFR63
 TSCA inventory status..... All components are listed.
 California Proposition 65..... *WARNING: This product contains a chemical known to the State of California to cause cancer. (Carbon black - airborne, unbound particles of respirable size).

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Review Date:..... 2021-11-05.
 Date of the latest revision of the safety .. 2016-09-12
 data sheet