



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: PF88204 Basecoat Reducer - Extra Slow**

### SECTION 01: IDENTIFICATION

Initial supplier identifier..... Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario L9T3Y5  
Tel (905) 878-4990 Fax (905) 878-1189

Product identifier..... PF88204 Basecoat Reducer - Extra Slow

Recommended use and restrictions on .. Paints.  
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES  
CALL CHEMTREC 1-800-424-9300. .

### SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Skin Irritant 2. Eye Irritation — Category 2A. Specific Target Organ Toxicity — Single Exposure — Category 3. (central nervous system). (narcotic effects). (respiratory system).

Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response ..... P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P302 + P352 - If on skin: wash with plenty of water. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell.

Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note ..... This product mixture has been classified based on its ingredients.

### SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS

| HAZARDOUS INGREDIENTS     | CAS #    | WT. % |
|---------------------------|----------|-------|
| Acetic acid, methyl ester | 79-20-9  | 30-60 |
| 4-Chlorobenzotrifluoride  | 98-56-6  | 15-40 |
| Propylene carbonate       | 108-32-7 | 5-10  |

<<The actual concentration(s) withheld as a trade secret>> .

**PRODUCT: PF88204 Basecoat Reducer - Extra Slow****SECTION 04: FIRST-AID MEASURES**

|                                                                       |                                                                                                                                                                                                                                                                                                                             |
|-----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye contact.....                                                      | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.                                                                                                                                                                                   |
| Skin contact.....                                                     | Immediately remove all contaminated clothing; flush skin with water for at least 15 minutes. Wash clothing before reuse. Obtain medical attention.                                                                                                                                                                          |
| Inhalation.....                                                       | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.                                                                                                                                                                           |
| Ingestion.....                                                        | Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Obtain medical attention immediately.                                                                                  |
| Most important symptoms and effects, ....<br>whether acute or delayed | Causes skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. High vapour concentrations may be irritating to the respiratory tract.                           |
| Additional information.....                                           | Treat victims symptomatically. If symptoms such as gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

**SECTION 05: FIRE-FIGHTING MEASURES**

|                                                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable and unsuitable extinguishing media                                                                  | Carbon dioxide, dry chemical, foam. Water spray. Do not use water in a jet.                                                                                                                                                                                                                                                                                                                                                                                                          |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Oxides of carbon (CO, CO <sub>2</sub> ). Hydrocarbon fumes and smoke.                                                                                                                                                                                                                                                                                                                                                                                                                |
| Special protective equipment and precautions for fire-fighters                                               | Extremely flammable. Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. |

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

|                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Methods and materials for containment and cleaning up               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Leak/spill.....                                                     | Isolate area and keep unauthorized people away. Do not walk through spilled material. Keep away from heat, sparks and flames. Eliminate all sources of ignition. Wear proper protective equipment. Ventilate area to remove the remaining vapours. Absorb with an inert dry material and place in an appropriate waste container. The spill area should then be washed down with soap and water to dilute and remove remaining traces of material. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. |
| Personal precautions, protective equipment and emergency procedures | Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Use non-sparking tools and equipment to pick up the spilled material.                                                                                                                                                                             |

**SECTION 07: HANDLING AND STORAGE**

|                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautions for safe handling.....                           | Keep away from heat, sparks, and open flame. Avoid skin and eye contact. Avoid breathing vapours or mist. Containers must be grounded and bonded. Do not use near sources of ignition, open flames or sparks. Do not cut, drill, weld or grind on or near the container. Open containers slowly to allow for any pressure build-up to escape. Keep containers closed when not in use. Employees should wash hands and face before eating or drinking. |
| Conditions for safe storage, including any incompatibilities | Keep away from heat, sparks, and open flames. Store in a cool, dry and well ventilated area. Store away from oxidizing and reducing materials.                                                                                                                                                                                                                                                                                                        |

**SECTION 08: EXPOSURE CONTROLS/PERSONAL PROTECTION**

| INGREDIENTS                   | TWA             | ACGIH TLV<br>STEL | PEL             | OSHA PEL<br>STEL | REL | NIOSH           |
|-------------------------------|-----------------|-------------------|-----------------|------------------|-----|-----------------|
| Acetic acid, methyl ester     | 200 ppm         | Not established   | 200 ppm         | Not established  |     | Not established |
| 4-Chlorobenzotrifluoride      | Not established | Not established   | Not established | Not established  |     | Not established |
| Propylene carbonate           | Not established |                   | Not established |                  |     | Not established |
| Personal protective equipment |                 |                   |                 |                  |     |                 |

**PRODUCT: PF88204 Basecoat Reducer - Extra Slow****SECTION 08: EXPOSURE CONTROLS/PERSONAL PROTECTION**

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Respiratory/type.....                 | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. Be sure to use NIOSH approved respirator or equipment. Do not exceed the use limits of the respirator.                                                                                                                                                                                                                                           |
| Eye/type.....                         | Chemical safety goggles. Chemical safety goggles and full faceshield if a splash hazard exists.                                                                                                                                                                                                                                                                                                                                                                                                            |
| Gloves/ type.....                     | Wear skin protection equipment. The selection of this equipment depends on the nature of the work to be done.                                                                                                                                                                                                                                                                                                                                                                                              |
| Clothing/type.....                    | Wear adequate protective clothes. Wear long sleeves and trousers to prevent dermal exposure.                                                                                                                                                                                                                                                                                                                                                                                                               |
| Footwear/type.....                    | Safety boots per local regulations.                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Other/type.....                       | Eye wash facility and emergency shower should be in close proximity. Employees should wash their hands and face before eating, drinking, or using tobacco products.                                                                                                                                                                                                                                                                                                                                        |
| Appropriate engineering controls..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. . Explosion-proof exhaust ventilation. |

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

|                                                    |                                                     |
|----------------------------------------------------|-----------------------------------------------------|
| Physical state.....                                | Liquid.                                             |
| Colour.....                                        | Clear to pale yellow.                               |
| Odour.....                                         | Pleasant. Aromatic.                                 |
| Odour threshold (ppm).....                         | 4.6 ppm.                                            |
| pH.....                                            | Neutral.                                            |
| Melting / Freezing point (deg C).....              | < -33 C.                                            |
| Initial boiling point / boiling range (deg C)..... | >55 C.                                              |
| Flash point (deg C), method.....                   | -15.6°C. (estimate; lowest flash point ingredient). |
| Evaporation rate.....                              | > 1.0.                                              |
| Flammability (solids and gases).....               | Not applicable.                                     |
| Upper flammable limit (% vol).....                 | 16.0.                                               |
| Lower flammable limit (% vol).....                 | 0.9.                                                |
| Vapour pressure (mm Hg).....                       | <. 179.5 mmHg @ 20°C.                               |
| Vapour density (air=1).....                        | >1.                                                 |
| Relative Density (Specific Gravity).....           | 1.066 - 8.89 lb/usg.                                |
| Solubility.....                                    |                                                     |
| Coefficient of water/oil distribution.....         | Not available.                                      |
| Auto ignition temperature (deg C).....             | Approx. 500.                                        |
| Decomposition temperature.....                     | Not available.                                      |
| Viscosity.....                                     | 12.8 seconds Zahn #2.                               |
| VOC.....                                           | 0 lb/usg - 0 g/mL.                                  |

**SECTION 10: STABILITY AND REACTIVITY**

|                                             |                                                                                            |
|---------------------------------------------|--------------------------------------------------------------------------------------------|
| Reactivity .....                            | Product is stable; hazardous polymerization will not occur. Avoid heat, sparks and flames. |
| Chemical stability.....                     | Stable at normal temperatures and pressures.                                               |
| Possibility of hazardous reactions.....     | Will not occur under normal temperature and pressure.                                      |
| Conditions to avoid, including static ..... | Avoid heat, spark, open flames. Electrostatic charge.                                      |
| discharge, shock or vibration               |                                                                                            |
| Incompatible materials.....                 | Strong acids. Strong bases. Strong oxidizers. Substances with an acid reaction.            |
| Hazardous decomposition products.....       | Oxides of carbon (CO,CO2).                                                                 |

**SECTION 11: TOXICOLOGICAL INFORMATION**

| INGREDIENTS                      | LC50                                                                                                                                                                         | LD50                                                   |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|
| Acetic acid, methyl ester        | 16000 ppm ( Rat ) 4 h                                                                                                                                                        | LD50 5001 mg/kg oral rat LD50 5001 mg/kg dermal rabbit |
| 4-Chlorobenzotrifluoride         | 4479 ppm                                                                                                                                                                     | >6,800 mg/kg rat oral; >2,700 mg/kg rabbit dermal      |
| Propylene carbonate              | Not available                                                                                                                                                                | >5000 mg/kg (oral, rat) >2000 mg/kg (dermal, rat)      |
| Route of exposure.....           | Eye contact. Skin contact. Inhalation.                                                                                                                                       |                                                        |
| Effects of acute exposure.....   | Causes skin irritation. Causes serious eye irritation. Irritating to mucous membranes and upper respiratory tract. Excessive inhalation of this product may cause dizziness. |                                                        |
| Effects of chronic exposure..... | Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.                                                                                     |                                                        |

**PRODUCT: PF88204 Basecoat Reducer - Extra Slow****SECTION 11: TOXICOLOGICAL INFORMATION**

Carcinogenicity of material..... The components of this product are not listed by IARC, NTP or regulated as a carcinogen by OSHA.  
 Reproductive effects..... No known reproductive effects.  
 Specific Target Organ Toxicity ..... May cause drowsiness or dizziness. May cause respiratory irritation. Damage to central nervous system.

**SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity..... No product data.  
 Persistence and degradability..... Not available.  
 Bioaccumulative potential..... No product data.  
 Mobility in soil..... Not available.  
 Other adverse effects..... Not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations. Do not heat or cut empty containers with electric or gas torch.

**SECTION 14: TRANSPORT INFORMATION**

TDG Classification..... UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.  
 DOT Classification (Road)..... UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (1 Liter). Refer to 49CFR 172.101 for additional non-bulk packaging requirements.  
 IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.  
 IMDG Classification (Marine)..... UN1263 - PAINT - Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.  
 Marine Pollutant..... No.  
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

**SECTION 15: REGULATORY INFORMATION**

CEPA status..... On Domestic Substances List (DSL).  
 TSCA inventory status..... All components are listed.  
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.  
 SARA Title III  
 Section 302 - extremely hazardous ..... Propylene oxide.  
 substances  
 Section 311/312 - hazard categories..... Fire hazard. Immediate health.  
 Section 313..... None above De minimus % limit.  
 EPA hazardous air pollutants (HAPS) ..... Propylene oxide.  
 40CFR63  
 California Proposition 65..... \*\*\* ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Propylene oxide). For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**SECTION 16: OTHER INFORMATION**

Prepared by: ..... REGULATORY AFFAIRS. Trivalent Data Systems Ltd. [www.trivalent.com](http://www.trivalent.com).  
 Telephone number: ..... (800) 387-7981.  
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.  
 Date of the latest revision of the safety data sheet .. OCT 23/2018