

RUSFRE®RUSFRE
604 McGEACHIE DRIVE
MILTON, ONTARIO, L9T 3Y5**PRODUCT: RF100016B INNER PANEL A/P RUSTPROOF BLACK 16GAL****SECTION 01: IDENTIFICATION**

Initial supplier identifier..... RUSFRE
604 McGeachie Drive
Milton
Ontario
L9T 3Y5

Product identifier..... RF100016B INNER PANEL A/P RUSTPROOF BLACK 16GAL

Recommended use and restrictions on .. Rust proofing.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 2 Reactivity: 0.

HMIS..... H: 2 F: 2 R: 0.

24 hour emergency number..... For transportation emergencies (in Canada) call CANUTEC 1-888-226-8832 (CAN-UTEC);
IN THE UNITED STATES CALL CHEMTREC 1-800-424-9300.
** For medical emergencies contact your local poison control centre **.

SECTION 02: HAZARD IDENTIFICATION

Signal Word..... WARNING.

Hazard Classification..... Flammable Liquid 3. Acute Toxicity (Oral) — Category 4. Acute Toxicity (Dermal) — Category 4. Acute Toxicity (Inhalation) — Category 4. Skin Irritation — Category 2. Eye Irritation — Category 2B. Specific Target Organ Toxicity — Single Exposure — Category 3. (respiratory system). Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 2. (Liver, Kidney).

Hazard Description..... H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H320 Causes eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. (Liver, Kidney).

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P301 + P312 If swallowed call a poison control centre. P330 Rinse mouth. P312 Call a POISON CENTER/doctor if you feel unwell. P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P332 + P313 - If skin irritation occurs get medical attention or advice.

Storage..... P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P405 Store locked up.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

PRODUCT: RF100016B INNER PANEL A/P RUSTPROOF BLACK 16GAL**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Mineral Spirits (Stoddard solvent)	8052-41-3	10-30
Sulfonic acids, petroleum, calcium salts	61789-86-4	1-5
Methanol	67-56-1	0.1-1

<<The actual concentration(s) withheld as a trade secret>>

SECTION 04: FIRST-AID MEASURES

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Immediately flush skin with plenty of soap and water. Remove contaminated clothing. Wash clothing before reuse. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, whether acute or delayed	Harmful if swallowed, in contact with skin or if inhaled. Causes skin and eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Methyl alcohol: The intoxication begins with central nervous system depression resulting in narcosis, followed by an asymptomatic latency period that usually lasts 12 to 24 hours. Metabolic acidosis sets in and symptoms such as headache, dizziness, nausea and vomiting appear. This is followed, in more serious cases, by abdominal and muscular pains as well as breathing difficulties. There are also disorders such as blurred vision, photophobia, impaired pupillary reflex and eye pain. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. This product contains ingredients that are suspected of damaging fertility or the unborn child.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO2, dry chemical. In cases of larger fires, water spray should be used. Do not use water in a jet.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Oxides of carbon (CO, CO2). Dense black smoke.
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up Leak/spill.....	Ventilate. Eliminate all sources of ignition. Avoid all personal contact. Evacuate all non-essential personnel. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.
Personal precautions, protective equipment and emergency procedures	Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Use non-sparking tools and equipment to pick up the spilled material.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....	Keep away from heat, sparks, and open flame. Ground handling equipment. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.
------------------------------------	---

PRODUCT: RF100016B INNER PANEL A/P RUSTPROOF BLACK 16GAL**SECTION 07: HANDLING AND STORAGE**

Conditions for safe storage, including any incompatibilities

Store away from all sources of heat and ignition. Store away from oxidizing and reducing materials. Store away from sunlight. Keep container closed when not in use.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Mineral Spirits (Stoddard solvent)	100 ppm	Not established	100ppm, 525 mg/m ³	Not established	Not established
	CA ON: 100 ppm (TWA)				
Sulfonic acids, petroleum, calcium salts	Not available		Not available		Not available
Methanol	200 ppm	250 ppm skin	200 ppm	Not established	200 ppm / STEL 250 ppm
	CA ON: 200 ppm (TWA), 250 ppm (STEL)				
Personal Protective Equipment					
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.				
Eye/type.....	Liquid chemical goggles. Chemical safety goggles and full faceshield if a splash hazard exists.				
Gloves/ type.....	Wear skin protection equipment. The selection of skin protection equipment depends on the nature of the work to be performed.				
Clothing/type.....	Wear adequate protective clothes.				
Footwear/type.....	Safety boots per local regulations.				
Other/type.....	Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products.				
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state.....	Gel.
Colour.....	Black.
Odour.....	Aromatic.
Odour threshold (ppm).....	0.2 ppm.
pH.....	Not applicable.
Melting / Freezing point (deg C)	
Initial boiling point / boiling range (deg C).	70-90.
Flash point (deg C), method.....	43 C. (Tag Closed Cup).
Evaporation rate.....	1.1.
Flammability (solids and gases).....	Flammable gel / paste.
Upper flammable limit (% vol).....	13.3.
Lower flammable limit (% vol).....	1.0.
Vapour pressure (mm Hg).....	Not available.
Vapour density (air=1).....	< 1.
Relative Density (Specific Gravity).....	1.01.
Pounds / USG.....	8.4 lbs/USG.
Solubility.....	Negligible.
Partition coefficient — n-octanol/water.....	Not available.
Auto ignition temperature (deg C).....	229.
Decomposition temperature.....	Not available.
Viscosity.....	4500 - 5000 cps.
% Volatile by weight.....	2.87 lbs/USG.
VOC (less water).....	3.52 lbs/USG.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Chemical stability.....	Stable at normal temperatures and pressures.
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.

PRODUCT: RF100016B INNER PANEL A/P RUSTPROOF BLACK 16GAL**SECTION 10: STABILITY AND REACTIVITY**

Conditions to avoid, including static Keep away from heat.
 discharge, shock or vibration
 Incompatible materials..... Strong oxidizing agents.
 Hazardous decomposition products..... Oxides of carbon (CO,CO₂). Dense black smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Mineral Spirits (Stoddard solvent)	5500 ppm (4 hrs)	5000 mg/kg (oral, rat)
Sulfonic acids, petroleum, calcium salts	Not available	> 20gm/kg (oral, rat)
Methanol	128.2 mg/L, 4h rat	420 mg/kg (oral); 5,628 mg/kg (rat oral); 15,800 mg/kg (rabbit dermal)
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	Irritating to eyes, skin and respiratory system. May be harmful if absorbed through the skin. Ingestion may cause adverse health effects.	
Effects of chronic exposure.....	Prolonged or repeated skin contact may cause drying or cracking of skin. Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. May cause nausea, headache, dizziness, and drowsiness. Chronic exposure to organic solvents may cause permanent brain and nervous system damage.	
Carcinogenicity of material.....	Asphalt may contain trace amounts of benzene, a chemical known to cause cancer.	
Reproductive effects.....	Methanol is teratogenic and embryotoxic in animals.	
Specific Target Organ Toxicity	May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure .	

SECTION 12: ECOLOGICAL INFORMATION

Environmental..... Do not allow to enter waters, waste water or soil.
 Persistence and degradability..... Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging . Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

SECTION 14: TRANSPORT INFORMATION

TDG Classification..... UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Stoddard Solvent) - Class 3 - Packing Group III. This product is a flammable liquid, Class 3, Packing Group III material with a flash point >37.8C and is exempt from the application of these regulations in non-bulk (< 450L) packaging as per TDG 1.33.

DOT Classification (Road)..... UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Stoddard Solvent) - Class 3 - Packing Group III. Refer to 49CFR 172.101 for additional non-bulk packaging requirements. With a flash point > 38C, this product may be reclassified as a combustible liquid and is exempt from application of the regulations in non-bulk packaging (< 450L) as per DOT 173.150 (f)(1)&(2).

IATA Classification (Air)..... UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Stoddard Solvent) - Class 3 - Packing Group III. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.

IMDG Classification (Marine)..... UN1993 - FLAMMABLE LIQUIDS, N.O.S. (Stoddard Solvent) - Class 3 - Packing Group III. EmS: F-E,S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.

Marine Pollutant..... No.

Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

CEPA status..... On Domestic Substances List (DSL).
 TSCA inventory status..... All components are listed.
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.

PRODUCT: RF100016B INNER PANEL A/P RUSTPROOF BLACK 16GAL**SECTION 15: REGULATORY INFORMATION**

Section 313..... Methanol.
EPA hazardous air pollutants (HAPS) Methanol.
40CFR63
California Proposition 65..... *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Benzene (D)). (Methanol). *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Benzene). For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
Telephone number:..... (800) 387-7981.
Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Review Date:..... 2021-11-15.
Date of the latest revision of the safety .. 2018-12-20
data sheet