

# Aircraft Paint Stripper PF 535

Aircraft Paint Stripper is newly formulated for the removal of aftermarket paint and coatings for metal parts. It will remove acrylics, epoxies, enamels, lacquers, polyurethanes and most other automotive finishes. Starts working in less than 15 minutes and cling well to vertical surfaces. It will lift multiple layers and is water rinseable. **DO NOT USE ON AIRCRAFT.** 

 PRODUCT
 SIZE

 PF 535
 531 g (18.75 oz) Aerosol

### READ ALL INSTRUCTIONS AND SAFETY PROCEDURES PRIOR TO USING!

IMPORTANT! This product contains hazardous materials.

Proper protective equipment should be used at all times. Please consult labels on each product as well as the safety data sheet for complete safe handling procedures and personal protection information.

NOTE: TEST ON A HIDDEN AREA BEFORE USING TO MAKE SURE THE PRODUCT PERFORMS TO YOUR SATISFACTION.

# DIRECTIONS FOR USE:

- 1. Mask all areas not to be stripped.
- 2. Shake can for 1 minute.
- 3. Wear eye protection, gloves and respirator.
- 4. Spray 15-20 cm (6 to 8 inches) away from surface.
- 5. Apply heavy even coat.
- 6. Allow remover to work until the finish is blistered or softened, generally within 15-20 minutes.
- 7. Remove paint with flexible plastic scrapper then flush with a mild solvent or water to remove any residue. Allow surface to dry before applying new finish.
- 8. Prime metal as soon as possible to prevent flash rust.

**NOTE:** This product may not be compatible with all surfaces and all condition surrounding application. Before applying to any surface, always test the product in a small inconspicuous area to ensure no damage will result. **NOT RECOMMENDED FOR USE ON FIBERGLASS, PLASTICS OR ANY OTHER SYNTHETIC SURFACE.** Rinse with water immediately after blistering of the coating to be removed. Work small area at a time. For best results, apply at temperatures between 65°F and 90°F, and avoid direct sunlight and strong breezes.

# TECHNICAL DATA:

	PF 535
Physical State	Aerosol
Color:	Clear
Odour:	Hydrocarbon odour
Solubility:	Slightly soluble in water
Flash point:	-104°C (-155.2°F)
Auto ignition temperature:	Not available



# Aircraft Paint Stripper PF 535

#### PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

## SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

#### TECHNICAL INFORMATION

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.

#### PRODUCT USE

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

## WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss. The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.